



*Changing the Way the World Works*



# **CALIFORNIA AIR TOOLS ULTRA QUIET & OIL-FREE AIR COMPRESSORS**

## **Features & Benefits**





- **Ultra Quiet**  
30% Less than Noise
- **Oil- Free**  
No Maintenance
- **Lightweight**  
Easy to Transport
- **Dual Piston Pump**  
Extra Long Life

# ULTRA QUIET & OIL-FREE DUAL PISTON PUMP / MOTORS

- **Oil-Free Pump**
  - No Maintenance
  - Use in Cold Temperatures
  - Use on Uneven Surfaces
- **Dual Piston Pump System**
  - More Efficient Air Delivery System
  - Faster Recovery Time
- **Low Amp Draw**
  - Energy Efficient
  - Less Speed only 1680 RPM
- **Longer Pump Life**
  - Extra Long Life Before Service





							
<b>Model</b>	SP-9415	SP-9414	SP-9413	CAT-MP100LF	CAT-MP120LF	SP-9421	SP-9407
<b>Motor</b>							
Motor Size	1/2 Hp	3/4 Hp	1.0 Hp	1.0 Hp	1.2 Hp	2.0 Hp	2.0 Hp
Volts	110	110	110	110	110	110	220
Amps	3.6	4.5	8.5	7.6	9	14	7
Decibels	56	58	60	60	60	70	70
<b>Air Delivery</b>							
40 PSI	1.9	2.4	3.1	4	6	6.4	6.4
90 PSI	1.1	1.5	2.2	3	3.8	5.3	5.3
MAX PSI	120	120	120	125	125	150	150
<b>Pump</b>							
Lubrication	Oil Free	Oil Free	Oil Free	Oil Free	Oil Free	Oil Free	Oil Free
Pump Type	Dual Piston	Dual Piston	Dual Piston	Dual Piston	Dual Piston	Dual Piston	Dual Piston
Wear	3000 hrs.	3000 hrs.	3000 hrs.	4000 hrs.	5000 hrs.	3000 hrs.	3000 hrs.
<b>Dimensions</b>							
Weight	17 lbs	21 lbs	21 lbs	23 lbs	23 lbs	40 lbs	40 lbs
Length	9.9"	9.9"	10.7"	10.5"	11.0"	12.6"	12.6"
Width	5.1"	5.1"	5.1"	5.5"	5.5"	6.1"	6.1"
Height	7.3"	7.3"	7.5"	8.5"	9.0"	11.7"	11.7"
<b>Certifications</b>							
Electrical	CE	CE	ETL / CE	N/A	N/A	ETL / CE	UL / CE
<b>Warranty</b>							
Months	12	12	12	12	18	12	12





## California Air Tools SP-9415 Ultra Quiet & Oil Free Air Compressor

- 0.5 HP (Running / Rated) Motor
- Oil – Free (Dual Piston) Pump
- 1.90 CFM @ 40 PSI
- 1.10 CFM @ 90 PSI
- 120 PSI Maximum
- 56 Decibels
- Thermal Overload Protector
- 3.6 Amps
- 3000 Hours Before Service
- CE





## California Air Tools SP-9414 Ultra Quiet & Oil Free Air Compressor

- 0.75 HP (Running / Rated) Motor
- Oil – Free (Dual Piston) Pump
- 2.40 CFM @ 40 PSI
- 1.50 CFM @ 90 PSI
- 120 PSI Maximum
- 58 Decibels
- Thermal Overload Protector
- 4.6 Amps
- 3000 Hours Before Service
- CE





## California Air Tools SP-9413 Ultra Quiet & Oil Free Air Compressor

- 1.0 HP (Running / Rated) Motor
- Oil – Free (Dual Piston) Pump
- 3.10 CFM @ 40 PSI
- 2.20 CFM @ 90 PSI
- 120 PSI Maximum
- 60 Decibels
- Thermal Overload Protector
- 8.5 Amps
- 3000 Hours Before Service
- ETL Certified





## **California Air Tools MP100LF (Industrial) Ultra Quiet & Oil Free Air Compressor Motor**

- **1.0 HP (Running / Rated) Motor**
- **Oil – Free (Dual Piston) Pump**
- **4.00 CFM @ 40 PSI**
- **3.00 CFM @ 90 PSI**
- **25% More Air Delivery**
- **120 PSI Maximum**
- **60 Decibels**
- **Thermal Overload Protector**
- **7.6 Amps**
- **4000 Hour Before Service**







## **California Air Tools MP120LF (Industrial) Ultra Quiet & Oil Free Air Compressor Motor**

- **1.2 HP (Running / Rated) Motor**
- **Oil – Free (Dual Piston) Pump**
- **6.00 CFM @ 40 PSI**
- **3.80 CFM @ 90 PSI**
- **120 PSI Maximum**
- **60 Decibels**
- **Thermal Overload Protector**
- **Japanese Bearings**
- **High-Density Teflon Coated cylinder**
- **9.0 Amps**
- **5000 Hours Before Service**





## California Air Tools SP-9421 Ultra Quiet & Oil Free Air Compressor

- 2.0 HP (Running / Rated) Motor
- Oil – Free (Dual Piston) Pump
- 6.40 CFM @ 40 PSI
- 5.30 CFM @ 90 PSI
- 150 PSI Maximum
- 70 Decibels
- Thermal Overload Protector
- 14.0 Amps
- 110v 60Hz
- 3000 Hours Before Service
- ETL Certified





## California Air Tools SP-90407 Ultra Quiet & Oil Free Air Compressor

- 2.0 HP (Running / Rated) Motor
- Oil – Free (Dual Piston) Pump
- 6.40 CFM @ 40 PSI
- 5.30 CFM @ 90 PSI
- 150 PSI Maximum
- 70 Decibels
- Thermal Overload Protector
- 7.5 Amps
- 220v 60Hz
- 3000 Hours Before Service

