

Two Stage Electric - Three Phase



Model	Part #	HP	Voltage/ Phase	Tank (Gal)	ACFM @ 100 psi	ACFM @ 175 psi	Max Pressure	Dim. In. L X W x H	Shipping Weight
338V	8090250026	5	208-230/3	80V	18.50	16.60	175 psi	39 x 24 x 77	457 lbs
338V4	8090252837	5	460/3	80V	18.50	16.60	175 psi	39 x 24 x 77	457 lbs
338H	8090250022	5	208-230/3	80H	18.50	16.60	175 psi	71 x 24 x 49	471 lbs
338H4	8090252845	5	460/3	80H	18.50	16.60	175 psi	71 x 24 x 49	471 lbs
338VE	8090250014	5	208-230/3	80V	18.50	16.60	175 psi	39 x 24 x 77	453 lbs
338VE4	8090250033	5	460/3	80V	18.50	16.60	175 psi	39 x 24 x 77	453 lbs
338HE	8090250023	5	208-230/3	80H	18.50	16.60	175 psi	71 x 24 x 49	481 lbs
338HE4	8090250030	5	460/3	80H	18.50	16.60	175 psi	71 x 24 x 49	481 lbs
338VL	8090250028	7.5	208-230/3	80V	25.25	22.28	175 psi	39 x 24 x 77	467 lbs
338VL4	8090250034	7.5	460/3	80V	25.25	22.28	175 psi	39 x 24 x 77	467 lbs
338HL	8090250024	7.5	208-230/3	80H	25.25	22.28	175 psi	71 x 24 x 49	481 lbs
338HL4	8090250031	7.5	460/3	80H	25.25	22.28	175 psi	71 x 24 x 49	481 lbs
338VLE	8090250029	7.5	208-230/3	80V	25.25	22.28	175 psi	39 x 24 x 77	477 lbs
338VLE4	8090250035	7.5	460/3	80V	25.25	22.28	175 psi	39 x 24 x 77	477 lbs
338HLE	8090250025	7.5	208-230/3	80H	25.25	22.28	175 psi	71 x 24 x 49	491 lbs
338HLE4	8090250032	7.5	460/3	80H	25.25	22.28	175 psi	71 x 24 x 49	491 lbs

Standard Features

- Solid Cast Iron Cylinder
- Start-Stop Pressure Switch Control
- ASME Code Tank and Safety Valves
- Fully Enclosed High Flow Belt Guard
- Oil Level Sight Glass
- 100% Factory Tested at Full Pressure
- Tri-Voltage Motors
- 2 Year Bumper to Bumper Warranty

All "Elite Series" Compressors include Magnetic Starter, Low Oil Switch, Automatic Tank Drain and Triple Pass Pump Mounted Aftercooler