

80 Gallon Hi-Flo - Single Stage - Cast Iron

FEATURES & BENEFITS

- High air flow, single stage – 14 CFM @ 90 PSI
- Cast iron, three cylinder, oil lubricated pump features
 - One-piece cast iron crankcase
 - Full cast iron cylinder body
 - Durable Swedish stainless steel flex leaf valves
 - Oil level sight glass
 - Easily accessible oil fill
 - 12" cast iron balanced flywheel
 - Large intake filter/silencers
- Heavy duty, 240 volt induction motor
- 155 PSI max pressure for optimum tool performance
- Large capacity, 80 gallon ASME* air receiver provides more air for longer run times on air tools such as ratchets, impacts, spray guns, hammers, etc
- Wire formed belt guard for more efficient cooling
- Shipped with synthetic oil for optimum performance and long life
- Supported by our Toll Free Customer Help Line



MODEL SPECIFICATIONS

Tank Size:	80 Gallon ASME*
Maximum Pressure:	155 PSI
CFM @ 40 PSI:	16.1
CFM @ 90 PSI:	14.0
Voltage:	240 Volt
Running HP:	4.7
Certifications:	UL & CSA
Warranty:	2 Year Limited

Dimensions: 31.5" x 34.75" x 77" • Weight: 354 lbs. • UPC: 8 46212 00575 0 • Pallet Qty: 1 • Truckload Qty: 54 (53' trailer)

*ASME - American Society of Mechanical Engineers Product style and configuration may vary.



MODEL: [ILA4708065.01](#)