

60 Gallon Cast Iron - Oil Lubricated - Belt Drive

FEATURES & BENEFITS

- Cast iron, twin cylinder, oil lubricated pump features
 - One-piece cast iron crankcase
 - Thermally stable cast iron cylinder body
 - Aluminum head & valve plate
 - Automotive style ball bearings
 - Durable Swedish stainless steel reed valves
 - Oil level sight glass
 - Easily accessible oil fill
 - 12" cast iron balanced flywheel
- Heavy duty, 240 volt induction motor for maximum performance and efficiency
- 155 PSI max pressure for optimum tool performance
- Large capacity, 60 gallon ASME* air receiver provides more air for longer run times on air tools such as ratchets, impacts, spray guns, hammers, etc
- Shipped with synthetic oil for optimum performance and long life
- Equipped with pressure gauge and on/off switch
- Supported by our Toll Free Customer Help Line



MODEL SPECIFICATIONS

Tank Size:	60 Gallon ASME*
Maximum Pressure:	155 PSI
CFM @ 40 PSI:	13.4
CFM @ 90 PSI:	11.5
Voltage:	240 Volt
Running HP:	3.7
Certifications:	UL & CSA
Warranty:	2 Year Limited



Dimensions: 31" x 27" x 69.25" • Weight: 247 lbs. • UPC: 8 46212 00156 1 • Pallet Qty: 1 • Truckload Qty: 69 (53' trailer)

*ASME - American Society of Mechanical Engineers Product style and configuration may vary.

MODEL: ILA3606056