

Hand Carry & Wheeled Portable



AIR COMPRESSORS Jenny®



Hand Carry

Standard Features

- Lightweight, compact and extremely portable
- Single stage, direct coupled, oil lubricated pump
- Cast iron cylinder for extended pump life
- Aluminum head for better heat dissipation
- Each unit is filled with Jenny Ultimate Blue Compressor Pump Oil
- Canister inlet filter with replaceable filter elements
- Forced ventilation cooling system
- Powder coated heavy duty steel tank and frame assembly
- Protectively mounted fittings
- Anti-vibration feet
- Air line regulator and two gauges for line and tank pressure
- Pressure relief safety valve
- Manual tank drain(s)
- Special unloading valves to assist in motor/engine starting



Electric Units

- Start/Stop pressure switch control set at 105-125 PSI
- On/Off Switch
- Thermal overload motor protection with manual reset
- 6 ft power cord



Model	HP	Tank Gallon	Drive	CFM @ 100 PSI	CFM @ 125 PSI
A2G246-HC4V	2	4.8	115 Volt	4.0	3.4
A2G246-HC5H		5.3			
AM780-HC2		1.5			
AM780-HC4V	4	4	Gas/Honda	4.3	3.8
AM840-4HG-HC4V				4.7	4.4

Gasoline Engine

- High quality pilot valve
- Pneumatic throttle idle control
- Constant run control set at 105-125 PSI
- Recoil start Honda GX Series OHV Engine



UL and CSA are not required for gas engine units.

Single Stage Wheeled Portable

Standard Features

- Heavy-duty single stage cast iron compressor pump
Made in Somerset, PA USA
- Splash lubricated
- Belt driven with a large flywheel for extra cooling and easier start-up
- Each unit is filled with Jenny Ultimate Blue Compressor Pump Oil
- Directional air shroud for reduced pump temperatures
- Totally enclosed heavy-duty belt guard
- 8 & 15 gallon tanks are low profile, powder coated twin tank receivers
- 17 and 30 gallon tanks are powder coated and ASME certified
- Oil sight glass
- Convenient lifting handles
- Anti-vibration feet
- Pneumatic tire(s)
- Protectively mounted fittings
- Manual tank drain(s)
- Large canister intake filter with replaceable filter elements
- Special unloading valves to assist in motor starting
- Stainless steel braided discharge hose
- Tank gauge
- Regulator and outlet pressure gauge
- Pressure relief safety valve
- Designed, tested and proven to meet the demands of the construction and rental industry

Electric Motor

- Constant run control set at 105-125 PSI
- High quality pilot valve
- Industrial/Commercial grade UL Listed electric motor
- Thermal overload motor protection
- 6 ft power cord



Model	Pump	HP	Tank Gallon	Power Supply	CFM@ 100 PSI	CFM@ 125 PSI		
K1A-8P	K	1	8	115 or 230 Volt 1 Phase	4.2	4.0		
K1A-15P			15					
K1A-17P			17					
K1A-30P			30					
K15A-8P	K	1.5	8		230 Volt 1 Phase	6.5	6.2	
K15A-15P			15					
K15A-17P			17					
K15A-30P			30					
K2A-8P	G	2	8			230 Volt 1 Phase	8.4	8.0
K2A-15P			15					
K2A-17P			17					
K2A-30P			30					
G3A-8P	G	3	8	230 Volt 1 Phase			13.8	13.5
G3A-15P			15					
G3A-17P			17					
G3A-30P			30					
G5A-8P	G	5	8		230 Volt 1 Phase		18.3	17.8
G5A-15P			15					
G5A-17P			17					
G5A-30P			30					
J5A-30P	J		30				24.0	23.0

Options

- Start-Stop control ■ Dual control
- Dual voltage switch ■ On-Off switch
- Two wheel option (8 & 15 gallon models)
- Discharge Unloader ■ Air line filter ■ Lubricator
- Other pressures available upon request



Air Compressors
E483335

Single Stage Wheeled Portable

Standard Features

- Heavy-duty single stage cast iron compressor pump
Made in Somerset, PA USA
- Splash lubricated
- Belt driven with a large flywheel for extra cooling and easier start-up
- Each unit is filled with Jenny Ultimate Blue Compressor Pump Oil
- Directional air shroud for reduced pump temperatures
- Totally enclosed heavy-duty belt guard
- 8 & 15 gallon tanks are low profile, powder coated twin tank receivers
- 17 and 30 gallon tanks are powder coated and ASME certified
- Convenient lifting handles
- Anti-vibration feet
- Pneumatic tire(s)
- Protectively mounted fittings
- Oil sight glass
- Manual tank drain(s)
- Large canister intake filter with replaceable filter elements
- Special unloading valves to assist in engine starting
- Stainless steel braided discharge hose
- Tank gauge
- Regulator and outlet pressure gauge
- Pressure relief safety valve
- Designed, tested and proven to meet the demands of the construction and rental industry



Model	Pump	HP	Tank Gallon	Drive	CFM @ 100 PSI	CFM @ 125 PSI
K5HGA-8P	K	5.5	8	Honda GX Gasoline Engine Recoil Start	8.9	8.6
K5HGA-15P			15			
K5HGA-17P			17			
K5HGA-30P			30			
C6HGA-8P	C	6.5	8		10.7	10.3
C6HGA-15P			15			
C6HGA-17P			17			
C6HGA-30P			30			
G9HGA-8P	G	9	8		16.2	15.6
G9HGA-15P			15			
G9HGA-17P			17			
G9HGA-30P			30			
J11HGA-30P	J	11	30	Electric Start	24.0	22.9
J13HGA-30P		13			28.4	27.1



Gasoline Engine

- Constant run control set at 105-125 PSI
- High quality pilot valve
- Pneumatic throttle idle control
- Honda GX Series OHV Engine

Options

- Two wheel option (8 & 15 gallon models)
- Air line filter ■ Lubricator ■ Electric start
- Discharge Unloader
- Other engine options available upon request
- Other pressures available upon request
- UL and CSA are not required for gas engine units.

Two Stage Wheeled Portable

Standard Features

- Heavy-duty two stage cast iron compressor pump
Made in Somerset, PA USA
- Splash lubricated
- Finned intercooler
- Belt driven with a large flywheel for extra cooling and easier start-up
- Each unit is filled with Jenny Ultimate Blue Compressor Pump Oil
- Directional air shroud for reduced pump temperatures
- Totally enclosed heavy-duty belt guard
- 8 & 15 gallon tanks are low profile, powder coated twin tank receivers
- 17 and 30 gallon tanks are powder coated and ASME certified
- Convenient lifting handles
- Oil sight glass
- Anti-vibration feet
- Pneumatic tire(s)
- Protectively mounted fittings
- Manual tank drain(s)
- Large canister intake filter with replaceable filter elements
- Special unloading valves to assist in motor/engine starting
- Stainless steel braided discharge hose
- Tank gauge
- Regulator and outlet pressure gauge
- Pressure relief safety valve
- Designed, tested and proven to meet the demands of the construction and rental industry

Electric

- Constant run control set at 145-175 PSI
- High quality pilot valve
- Industrial/Commercial grade UL Listed electric motor
- Thermal overload motor protection
- 6 ft power cord

Model	Pump	HP	Tank Gallon	Power Supply	CFM @ 100 PSI	CFM @ 175 PSI
GT5B-8P2	GT	5	8	230V 1 Phase	15.5	15.2
GT5B-15P2			15			
GT5B-17P			17			
GT5B-30P			30			
W5B-30P	W		30		21.0	17.9



GT5B-8P2

GT9HGB-15P2

GT9HGB-17P

Options (Electric Motor)

- Start-Stop control ■ Dual control ■ Dual voltage switch
- On-Off switch ■ Two wheel option (8 & 15 gallon models)
- Air line filter ■ Lubricator
- Other pressures available upon request



GT5B-30P

Gasoline Engine

- Constant run control set at 145-175 PSI
- High quality pilot valve
- Pneumatic throttle idle control
- Honda GX Series OHV Engine

Model	Pump	HP	Tank Gallon	Drive	CFM @ 100 PSI	CFM @ 175 PSI
GT9HGB-8P2	GT	9	8	Honda GX Gas Engine Recoil Start	15.7	15.4
GT9HGB-15P			15			
GT9HGB-17P			17			
GT9HGB-30P			30			
W11HGB-30P	W	11	30	Electric Start	21.0	17.6
W13HGB-30P		13				

Options (Gas Engine)

- Two wheel option (8 & 15 gallon models)
- Discharge Unloader ■ Air line filter ■ Lubricator ■ Electric start
- Other engine options available upon request
- Other pressures available upon request

UL and CSA are not required for gas engine units.

Special Portable Compressor

Standard Features

- Heavy-duty single or two stage cast iron compressor pump
Made in Somerset, PA USA
- Splash lubricated
- Belt driven with a large flywheel for extra cooling and easier start-up
- Finned intercooler (two stage only)
- Centrifugal unloader (two stage only)
- Each unit is filled with Jenny Ultimate Blue Compressor Pump Oil
- Totally enclosed heavy-duty belt guard
- Directional air shroud for reduced pump temperatures
- Protectively mounted fittings
- Manual tank drain(s)
- Large canister intake filter with replaceable filter elements
- Oil sight glass
- All tanks are powder coated and ASME certified
- High quality special unloading valves to assist in engine starting
- Stainless steel braided discharge hose
- Tank gauge
- Regulator and outlet pressure gauge
- Pressure relief safety valve
- Constant run control
Single stage set at 105 – 125 PSI
Two stage set at 145 – 175 PSI
- Pneumatic throttle idle control
- Honda GX Series OHV Engines except for the 18 HP which features the Kohler OVH V-Twin Engine
- Designed, tested and proven to meet the demands of the construction and rental industry

Skid Mount Single Stage

Model	Pump	HP	Tank Gallon	Drive	CFM @ 100 PSI	CFM @ 125 PSI
G9HGA-SM	G	9	30	Recoil	16.4	16.0
J11HGA-SM	J	11		Electric	24.0	22.9
J13HGA-SM		13			28.4	27.1

Two Stage

Model	Pump	HP	Tank Gallon	Drive	CFM @ 100 PSI	CFM @ 175 PSI
W11HGB-SM	W	11	30	Electric Start	21.0	17.6
W13HGB-SM		13			24.8	20.8
U18KGB-SM	U	18			41.0	34.7

Trailer Two Stage

Model	Pump	HP	Tank Gallon	Drive	CFM @ 100 PSI	CFM @ 125 PSI
W11HGB-PT	W	11	30	Electric Start	21.0	17.6
W13HGB-PT		13			24.8	20.8
U18KGB-PT	U	18			41.0	34.7

Options

- Air line filter ■ Lubricator ■ Electric start ■ Discharge Unloader
Other engine options available upon request ■ Other pressures available upon request

UL and CSA are not required for gas engine units.



W11HGB-SM

Service Vehicle

Standard Features

- Heavy-duty two stage cast iron compressor pump
Made in Somerset, PA USA
- Splash lubricated
- Belt driven with a large flywheel for extra cooling and easier start-up
- Finned intercooler (two stage only)
- Centrifugal unloader (two stage only)
- Oil sight glass
- Each unit is filled with Jenny Ultimate Blue Compressor Pump Oil
- Directional air shroud for reduced pump temperatures
- Totally enclosed heavy-duty belt guard
- Powder coated ASME certified receivers
- Protectively mounted fittings
- Bucket high manual and bottom mounted tank drain
- Large canister intake filter with replaceable filter elements
- High quality special unloading valves to assist in engine starting
- Stainless steel braided discharge hose
- Tank gauge
- Pressure relief safety valve
- Constant run control
Single stage set 105 – 125 PSI
Two stage set 145 – 175 PSI
- Pneumatic throttle idle control
- Honda GX Series OHV Engines except for the 18 HP which features the Kohler OVH V-Twin Engine
- Designed, tested and proven to meet the demands of the construction and rental industry



J11HGA-30T

Single Stage

Model	Pump	HP	Tank Gallon	Drive	CFM @ 125 PSI	CFM @ 150 PSI
K5HGA-30T	K	5.5	30	Recoil Start	8.6	7.9
C6HGA-30T	C	6.5			10.3	9.6
G9HGA-30T	G	9			16.0	14.9
G11HGA-30T		11		18.3	17.3	
J11HGA-30T	J	13		Electric Start	24.0	22.9
J13HGA-30T					28.4	27.1



K5HGA-30T

Two Stage

Model	Pump	HP	Tank Gallon	Drive	CFM @ 125 PSI	CFM @ 175 PSI
GT9HGB-30T	GT	9	30	Recoil Start	15.7	15.4
GT11HGB-30T		11			16.5	16.3
W11HGB-30T	W	13		Electric Start	19.8	17.6
W13HGB-30T			23.4		20.9	
U18KGB-80T*	U	18	80		39.5	34.7

*Fuel tank sold separately



GT11HGB-30T

Options

Air line filter ■ Lubricator ■ Electric start
Discharge Unloader

Other engine options available upon request
Other pressures available upon request

UL and CSA are not required for gas engine units.



LOCATION

AIR COMPRESSORS **Jenny**

Jenny Products, Inc.
850 North Pleasant Avenue
Somerset, PA 15501-1069
Phone 814-445-3400
Fax 814-445-2280
www.jennyproductsinc.com
www.jennycompressor.com