

Professional

Single Stage Belt Drive Series

- Oil lubricated, single stage cast iron pumps.
- Single phase induction motors with overload protection.
- Portable units feature built-in pressure regulator and quick coupler for pressure control of outlet air, and steel wheels with ball bearing and no-flat tires for best mobility.
- 1/2" outlet ball valve and 1/4" drain ball valve on 60 gal. vertical tank.
- Compressors with 60 gallon vertical tank are available in accessories such as automatic water drain, vibration damper, and high flow heavy duty regulator filter.
- Ideal for home and professional applications.



PUK-2008MDC



PK-2011VP



PK-5020



PK-5020VP



PK-6060V



PK-6560V



PK-7060V

Model #	Electric Motor			Pump R.P.M.	Max. Working P.S.I.	FAD-CFM		Tank			Weight lbs	Remark
	HP	R.P.M.	Volt. Phase Amp.			40psi	90psi	GAL.	Style	CODE		
PUK-2008MDC	2	3450	☑ 115/230 Single 19/9.5	980	135	8.5	7.4	8	Twin Portable		200	Dual Control / CSA
PK-2011VP	1	1720	☑ 115/230 Single 13/6.5	1040	135	3.8	3.0	11	Vertical Portable	ASME	116	CSA
PK-5020	2	3450	☑ 115/230 Single 14/7	1150	135	6.1	5.0	20	Horizontal Portable	ASME	194	CSA
PK-5020VP	2	3450	☑ 115/230 Single 14/7	1150	135	6.1	5.0	20	Vertical Portable	ASME	183	CSA
PK-6060V	3	3450	208-230 Single 16.6-15	980	135	12.6	11.3	60	Vertical	ASME CRN	305	
PK-6560V	5	3450	208-230 Single 23-21	1180	135	17	15.5	60	Vertical	ASME CRN	325	Motor Starter Optional
PK-7060V	6.5	3450	208-230 Single 28-24	1130	135	21	19.5	60	Vertical	ASME CRN	360	Motor Starter Optional

☑ Dual voltage motors, require rewiring by customers if 230V is needed. 230V plug is not included and needed to be purchased by customers to meet local code. *230V plug is not sold by Puma.