



**MODEL FC1250LS3**  
1.5 HP SINGLE STAGE COMPRESSOR  
DIRECT DRIVE



**ROLAIR STANDARD FEATURES**

**PUMP:** ROLAIR Quality, Single Stage, Ball Bearings, Cast-Iron Cylinder, Stainless Steel Reed Valves and Splash Lubrication Ensure Longer Life.  
**Low RPM for Quiet Operation**

**MOTOR:** 1.5 HP, 1700 RPM, Low Amp Draw, Overload Protection with Manual Reset, 115 Volt, 60 Hz, Heavy-Duty/Industrial Grade with Ball Bearings for Greater Durability.

**SPECIFICATIONS**

MODEL	MOTOR HP	# OF CYLS.	CU.FT. DISPLACED	CU.FT. FREE AIR@100 PSI	TANK CAP. (GAL.)	DIMENSIONS (L X W X H)	APPROX. SHIPPING WEIGHT
FC1250LS3	1.5	1	3.9	2.9	2.5	12" x 9" x 18"	38 lbs.

**STANDARD EQUIPMENT**

- Start/Stop Pressure Switch with On/Off Lever
- Air Line Regulator and Pressure Gauge
- Compact/Lightweight Tank Design
- Tank Pressure Gauge
- Safety Relief Valve
- Replaceable Filter Cartridge
- Initial 6 oz. Oil Fill Included
- Low Amp Motor



**ROLAIR SYSTEMS**

606 S. LAKE ST > P O BOX 346 > HUSTISFORD WI 53034-0346  
SALES FAX: 920.349.3691 > SERVICE FAX: 920.349.8861  
PHONE: 920-349-3281  
[www.rolair.com](http://www.rolair.com)