



New EMAX Regenerative Desiccant Compressor Air Dryer up to 260 CFM



Features:

- Low power consumption 115-240V single phase
- CE/UL approved
- Ambient air temp: Min 34F / Max 122F
- Inlet Temp: Min 40F / Max 120F
- Programmable controller, remote start-stop connection
- Can be mounted to the floor or wall with adjustable mounting brackets
- designed to remove moisture from compressed air by utilizing state of the art technology to obtain dewpoints of -40F and by appropriate de-rating -100F PDP.
- High quality components
- Quick and easy connections
- 2 Year warranty

Model	CFM	INLET-OUTLET	INLET PRESSURE	AMBIENT TEMP	VOLTAGE	WEIGHT
EDRDES1150025	20	½" NPT	60 MIN/ 230 MAX	34 MIN/ 122 MAX	115V	92
EDRDES1150045	45	1 ½" NPT	60 MIN/ 230 MAX	34 MIN/ 122 MAX	115V	156
EDRDES1150110	110	1 ½" NPT	60 MIN/ 230 MAX	34 MIN/ 122 MAX	115V	292

1000 Cass Drive
 Englewood, OH 45315
 Toll Free: 866-294-4153
 Fax: 937-540-1157

www.emaxcompressor.com

*2 year warranty

