

		QP-7.5	;					
HP	7.5		cfm@17	'5 psi	22.6			
Low Pressure_Bor	4.5"		Pump S	peed	1026			
High Pressure_Bor	2.5"							
Stroke	3"				80 Gal	V	80 Gal H	
Max Working Pres	175		Dims (Lx	(WxH)	37X24	X74	70X23X74	
Inlet Size	1" NPT		Weight		720		740	
Air Outlet Size	3/4" BALL VALVE							
Min/Max RPM	500-1060 RPM							
Pump Life	50,000 HRS	Tank Pressure		essure	200 ps	i		
Duty Cycle	100%			Tank Fill Time		5.6 min		
Lubrication	Quin-Cip							
Sump Capacity	1.93 qts. (1.83 lit.)		Standard Warranty		Factory - 12 months parts / 12			
Noise _dB(A)			Extended Warr		3-Year Pump/ 2-Year Packa			
Min operating_Temp	0 deg F		EWK part number		EWK-6			
Max operating_Temp	104 deg F		EWK Contents		1 Air Filter, 3 Oil Filters, 6 qts Quin-Cip D			
			*Duplex unit owners must purchase two (2) EWK kits *Engine-driven unit extended warranty is on air compressor only, "less engine". See engine manufacturer for warranty coverage.					
	Voltage: 120/1	230/1	200/3	230/3	460/3	575/3		
	Amp Draw:	40	25.3	22	11	9		

^{*}Applicable data doubled for Duplex models