



SPECIFICATION SHEET

Product	Electric Powered Lubricated Screw Air Compressor	Type :EN3 208-230V/60HZ	Date(Org):20/03/2015
Doc. Category :	Marketing	Revision : R13	Date(Rev):08/05/2018
S.No	Description	Units	Data
A	Model	-	EN3-125 EN3-150
B	TPL Number	-	S013456 S013457
1	Free air delivery - FAD	cfm	13.5 13.1
		m3/min	0.38 0.37
2	Working pressure	psi.g	125.0 150.0
3	Unloading pressure	psi.g	128.0 153.0
4	Cut in pressure	psi.g	103.0 128.0
5	Airend shaft power	hp	4.16 4.70
		kW	3.10 3.51
6	Package input power @ full load	hp (kW)	5.13(3.83) 5.80(4.33)
7	Package input power @ zero flow	hp (kW)	2.05(1.53) 2.32(1.73)
8	Specific power consumption @ full load	kW/100cfm	28.37 33.03
9	Capacity control system	-	LOAD / UNLOAD
10	Nominal power supply conditions	-	230V(+/-10%),60HZ(+/-5%)Combined(+/-10%),1phase
11	Main motor rating	hp (kW)	5(3.73)Normal rating with SF 1.0 Continuous duty
12	Type of motors (main drive & cooling fan drive)	-	1 Ph Squirrel cage induction motor & 1 Ph fan motor
13	Insulation and protection of main motor	-	Class F / IP 55
14	Rated speed of main motor	rpm	3500
15	Frame size / Mounting type	-	184T / B35
16	Efficiency of main motor/Efficiency class	-	83%/NEMA-PREMIUM
17	Type of starter for main motor	-	Direct Online Starter
18	Fan motor rating per fan x No. of fans	hp (kW)	0.127(0.095) x 1fan
19	Rated speed of fan motor	rpm	3200
20	Max allowable package current with fan at nominal power supply	Amps	23
21	Flow rate of cooling air @ static pressure (Pa)	cfm	625 @ 0 Pa
22	Oil recommended	-	ELGI AIRLUBE UT Synthetic
23	Capacity of seperator tank (full volume)	gal	0.634
24	Tank oil fill capacity	gal	0.422
25	Oil carry over	ppm	3
26	Reference conditions - ambient & altitude	°F/ ft	113 and 3280
27	Discharge oil temperature	°F	Minimum: Above PDP at given pr. & 90% RH
		°F	Maximum: Ambient +104.4
28	Maximum allowable air temperature at outlet	°F	Less than Ambient+27
29	Noise level of the compressor	dB (A)	61+3
30	Air outlet port size	inch	3/8" NPT
31	Overall dimensions of the unit, L x B x H	inch	24.21 x 28.15 x 33.26
32	Overall dimensions with packing, L x B x H	inch	27.95x 30.7 x 45.27
33	Package nett. weight (Dry condition)	lbs	352
34	Package gross weight with packing	lbs	381
35	Reference standard for FAD and SPC	-	ISO 1217- Annexure 'C '
36	Reference standard for noise level	-	ISO 2151, Second Edition
37	Reference standard for air purity	-	ISO 8573-1

Note:-

Prepared By	ARAVINTH N	Approved By	JAYARAJ B
-------------	------------	-------------	-----------

All data and information in this sheet are confidential and property of ELGI EQUIPMENTS LIMITED

This is system generated document and hence signature is not required