



SPECIFICATION SHEET

Product	Electric powered lubricated screw air compressor	Type :EG22 208-230/460V /	Date(Org):24/06/2017
Doc. Category :	Marketing	Revision : R05	Date(Rev):28/05/2019
S.No	Description	Units	Data
A	Model	-	EG 22-100 EG 22-125 EG 22-150 EG 22-175
B	TPL Number	-	S014063 S014064 S014065 S014066
1	Free air delivery - FAD	cfm	143 134 116 96
		m3/min	4.05 3.79 3.28 2.72
2	Working pressure	psi.g	100.0 125.0 150.0 175.0
3	Unloading pressure	psi.g	107.0 132.0 157.0 182.0
4	Package Input power @ 100% flow	hp (kW)	35.32(26.35) 37.32(27.84) 38.40(28.64) 35.17(26.24)
5	Package input power @ zero flow	hp (kW)	9.38(7.00) 10.06(7.50) 9.38(7.00)
6	Specific power consumption @ full load	kW/100cfm	18.43 20.78 24.69 27.33
7	Capacity control system	-	Load/Unload
8	Nominal power supply conditions	-	208-230 / 460V (+/-10%), 60Hz(+/-5%), 3 Phase
9	Main motor rating	hp (kW)	30.0(22.0)Normal Rating with SF1.2 Continuous duty
10	Type of motors (main drive & cooling fan drive)	-	Squirrel Cage Induction - TEFC & Cooling Fan Integrated Motor
11	Insulation and protection of main motor	-	Class F / IP55
12	Frame size / Mounting type	-	286T / B35
13	Efficiency class of main motor	-	93.6%/NEMA-PREMIUM
14	Type of starter for main motor	-	Automatic star delta
15	Fan motor rating per fan x No. of fans	hp (kW)	0.38(0.28) - 208-230V / 0.40(0.30)-460V X 2 Fans
16	Rated speed of fan motor	rpm	1560 (208V-230V) / 1630 (460V)
17	Max allowable package current with Fan at nominal power supply	Amps	94.6 (208V) / 85.7 (230V) / 42.9 (460V)
18	Type of coupling	-	Flexible jaw coupling with snap wrap element
19	Flow rate of cooling air @ static pressure (Pa)	cfm	3400 @ 70
20	Oil recommended	-	ELGI AIRLUBE UT SYNTHETIC
21	Capacity of seperator tank (full volume)	gal	4.8
22	Total oil fill capacity	gal	2.6 2.4
23	Oil carry over	ppm	<1.0
24	Reference conditions - ambient & altitude	°F/ ft	95 & 3280
25	Discharge oil temperature	°F	Minimum: Above PDP at given pr. & 90% RH
		°F	Maximum: Ambient +111.6
26	Maximum allowable air temperature at outlet	°F	Ambient +18
27	Noise level of the compressor	dB (A)	69
28	Air outlet port size	inch	1" NPT MALE THREAD
29	Overall dimensions of the unit, L x B x H	inch	56 X 28 X 58
30	Overall dimensions with packing, L x B x H	inch	59.8 X 35.4 X 62.6
31	Package nett. weight (dry condition)	lbs	1433
32	Package Gross Weight with packing	lbs	1521
33	Reference standard for FAD and SPC	-	ISO 1217- Annexure 'C '
34	Reference standard for noise level	-	ISO 2151, Second Edition
35	Reference standard for air purity	-	ISO 8573-1

Note:-

Prepared By	HARI HARAN R.B	Approved By	SUBRAMANIAN K
-------------	----------------	-------------	---------------

All data and information in this sheet are confidential and property of ELGI EQUIPMENTS LIMITED

This is system generated document and hence signature is not required