Two Stage Gasoline

8-Gallon

Ideal for both contractors and remodelers this two stage air compressor provides a reliable air source on remote jobsites. This model allows for more air to be stored for future use while generating less



- Stainless-steel braided discharge hose
- Large canister intake filter

Engine

- Industrial Honda OHV, Kohler OHV or Subaru OHC engine
- Pneumatic idle control to conserve fuel
- Engine oil drain

Frame

- Powder coated 8-gallon twin tank receivers
- 3/16-inch base plate to reduce vibration
- 14-gauge powder coated two-piece belt guard with 1/4-turn release for quick access to belts
- Convenient lifting handles
- Two pneumatic tires and steel hubs
- Heavy-duty axle

Components

- Regulator and two gauges for tank and outlet pressure
- Manual drain valves for proper maintenance
- Belt tightening system pulls engine straight to ensure constant belt alignment
- 16.5-inch fly wheel for extra cooling and longer life
- Quality pilot valve unloader

Warranties







	MODEL NUMBER	CFM @ PSI*	DISPLACEMENT/ENGINE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
	AM2-PH09-08M	17.2 @ 175	270cc Honda OHV	44in.x26in.x31in.	330 lb.	260 lb.
	AM2-PK95-08M	17.2 @ 175	277cc Kohler OHV	44in.x26in.x31in.	330 lb.	260 lb.
	AM2-PR09-08M	17.2 @ 175	265cc Subaru OHC	44in.x26in.x31in.	330 lb.	260 lb.

*Equipped with 150-PSI maximum rated regulator.

ACCESSORIES & OPTIONS

ACCESCITIES & OF HORS					
PART NUMBER	DESCRIPTION	FITS MODELS			
AW-6000-1002	Equipment cover - Keeps your equipment clean, dry and looking like new, made from 600-denier vinyl-backed polyester, water resistant, drawstrings to secure cover	All models			
AX-0003	Manual drain metal bowl - Drains moisture from air system	All models			
AX-0015	Electric start (battery and cables not included) - For easy starting	AM2-PH09-08M			
AX-0041	Electric start (battery and cables not included) - For easy starting	AM2-PR09-08M			
Consult Factory	Cable throttle control - Automatically throttles down engine to conserve fuel	Honda & Subaru models			