

ROTARY SCREW AIR SYSTEM PACKAGE UNITS WITH VSD CAPABILITY



Since 1977

Energy efficiency & MAXimum Performance

KEY FEATURES

- NEW maintenance free, High Temperature refrigerated Air Dryer
- Heavy duty steel cabinet
- Environmentally friendly 404A refrigerant



- Patent Pending Swing Arm Mount for quick and easy maintenance
- 120 Gallon ASME air receiver



www.EmaxCompressor.com
1000 Cass Drive
Clayton OH 45315
Toll Free: 866-294-4153
Fax: 937-540-1150
sales@emaxcompressor.com



BALDOR MOTORS AND DRIVES



Coalescing Filter –
1ppm with auto drain

- Precision engineered Rotary Air-End
- Advanced PLC Controller monitors oil, temp, hours, filtration & remote start/stop

Benefits:

- Automatic Tank Drain-Eliminates the need for daily maintenance
- Standard Y/Delta Soft Start Motor –Reduces Energy demand and amp draw on start up
- Available in 208/230/460/575 Voltage



Model Number	ERSK070001	ERSK100001	ERSK070003	ERSK100003	ERSK150003
Variable Speed Drive Included	No	No	No	No	No
Motor Horse Power	7.5	10	7.5	10	15
Low Motor RPM	1750	1750	1750	1750	1750
Compressor SCFM@100 PSI	29	45	29	45	62
Pump Model	B-40	B-60	B-40	B-60	B-60
Power (Voltage)	208/230	208/230	208/230/460/575	208/230/460/575	208/230/460/575
Dryer SCFM	28	56	28	56	91
Tank Size (gal)	120	120	120	120	120
Coalescing filter	65 CFM	65 CFM	65 CFM	65 CFM	65 CFM
SHIPPING WEIGHT(lbs)	1700	1725	1700	1725	1825
DIMENSIONS: LxWxH (inch)	80" x 38" x 80"	80" x 38" x 80"	80" x 38" x 80"	80" x 38" x 80"	83" x 38" x 87"

10YR – Limited Warranty on Air End Pump with purchase of annual service kit
5YR – Limited Warranty on Cabinet , Motor & Heat exchanger
2YR – Limited Warranty on all other parts



ASME International