



SINGLE STAGE
Solid CAST IRON piston pumps

Since 1977

Energy efficiency & MAXimum performance

PISTON SERIES PUMPS

- Quiet, low RPM Solid Cast Iron construction for extended life - up to 50,000 hours*



Ram-Tek: Solid Steel, heavy gauge rods for maximum performance & durability



Easily accessible, concentric disc valves insure trouble free maintenance and durability



Industrial Grade Ball Bearings for maximum performance and extended pump life

Contact:



www.EmaxCompressor.com
1000 Cass Drive
Clayton, Ohio 45315
Toll Free: 866-294-4153
Fax: 937-540-1150
sales@emaxcompressor.com



Built in HEAD UNLOADERS
for continuous run applications

APP2V0732S

APP3Y0518S

APP2V0313S

Oil level site glass



Engineered & Tested In The USA

Features & Benefits

- **Cool-Tek:** The coolest running compressor pumps in the industry - 35% lower operating temperature reduces moisture build up & extends pump life
- **Flow-Tek:** Concentric Disc Valves deliver maximum air flow and reliability with low replacement costs

| Model | APP2V0313S | APP3Y0518S | APP2V0732S |
|-------------------|------------------|-----------------|------------------|
| CFM Displacement | 13 | 18 | 32 |
| CFM @ 100 PSI | 10.2 | 14.1 | 18 |
| Maximum PSI | 145 | 145 | 145 |
| Pump RPM | 850 | 950 | 680 |
| Noise DB(A) | 75 | 75 | 74 |
| Bolt Pattern | 8 3/16" x 4 5/8" | 8 1/4" x 5 1/4" | 10 1/4" x 5 3/8" |
| Belt Type | A | A | B |
| Belt Number | 1 | 2 | 2 |
| Outlet | NPT 1/2" | NPT 1/2" | NPT 3/4" |
| Weight (lbs.) | 60 | 75 | 121 |
| Dimensions: LxWxH | 16" x 12" x 14" | 19" x 15" x 16" | 21" x 15" x 18" |

* Based on B-10 Bearing Rating

2 YR - Limited warranty on oil-lubricated pumps sold separately



PIXPUMPS01 10-09