



Piston Technical Data Sheet

QP-10

HP	10	cfm@175 psi	35
Low Pressure_Bor	5"	Pump Speed	968
High Pressure_Bor	2.75"		
Stroke	3.5"	120 Gal V	120 Gal H
Max Working Pres	175	Dims (LxWxH)	40X30X75 78X28X55
Inlet Size	1-1/4 NPT	Weight	850 850
Air Outlet Size			
Min/Max RPM	550-1000 RPM		
Pump Life	50,000 HRS	Tank Pressure	200 psi
Duty Cycle	100%	Tank Fill Time	5.5 min
Lubrication	Quin-Cip		
Sump Capacity	2.81 qts. (2.66 lit.)	Standard Warranty	Factory - 12 months parts / 12
Noise _dB(A)		Extended Warr	3-Year Pump/ 2-Year Packa
Min operating_Temp	0 deg F	EWK part number	EWK-7
Max operating_Temp	104 deg F	EWK Contents	1 Air Filter, 3 Oil Filters, 9 qts Quin-Cip D

\*Duplex unit owners must purchase two (2) EWK kits  
 \*Engine-driven unit extended warranty is on air compressor only, "less engine". See engine manufacturer for warranty coverage.

Voltage:	120/1	230/1	200/3	230/3	460/3	575/3
Amp Draw:	-	-	32.2	28	14	11

\*Applicable data doubled for Duplex models