



SPECIFICATION SHEET

Product	Electric Powered Lubricated Screw Air Compressor	Type :EN18 208-230/460V/60HZ	Date(Org):30/11/2012
Doc. Category :	Marketing	Revision : R07	Date(Rev):05/06/2018
S.No	Description	Units	Data
A	Model	-	EN18-100 EN18-125 EN18-150 EN18-175
B	TPL Number	-	S012506 S012455 S012507 S012508
1	Free air delivery - FAD	cfm	113 99 93 82
		m3/min	3.20 2.79 2.63 2.32
2	Working pressure	psi.g	100.0 125.0 150.0 175.0
3	Unloading pressure	psi.g	103.0 128.0 153.0 178.0
4	Cut in pressure	psi.g	74.0 99.0 124.0 149.0
5	Airend shaft power	hp	28.55 26.00 28.55
		kW	21.30 19.40 21.30
6	Package input power @ full load	hp (kW)	31.46(23.47) 28.72(21.43) 31.46(23.47)
7	Package input power @ zero flow	hp (kW)	7.87(5.87) 10.40(7.76) 7.87(5.87)
8	Specific power consumption @ full load	kW/100cfm	20.77 21.75 25.24 28.63
9	Capacity control system	-	LOAD / UNLOAD
10	Nominal power supply conditions	-	208 -230/460 V(+/-10%), 60Hz (+/-5%), 3 Phase
11	Main motor rating	hp (kW)	25(18.65)Normal rating with SF 1.15 Continuous duty
12	Type of motors (main drive & cooling fan drive)	-	3Ph squirrel cage induction motor and 3Ph fan motor
13	Insulation and protection of main motor	-	Class F / IP 55
14	Rated speed of main motor	rpm	3550
15	Frame size / Mounting type	-	256T / B3
16	Efficiency of main motor/Efficiency class	-	92.80%/NEMA-PREMIUM
17	Type of starter for main motor	-	Star Delta
18	Fan motor rating per fan x No. of fans	hp (kW)	0.35(0.26) x 2fans
19	Rated speed of fan motor	rpm	1490
20	Max allowable package current with fan at nominal power supply	Amps	75.4 - 68.4 / 34.3
21	Flow rate of cooling air @ static pressure (Pa)	cfm	4120 @ 0 Pa
22	Oil recommended	-	ELGI AIRLUBE UT Synthetic
23	Capacity of seperator tank (full volume)	gal	7.656
24	Tank oil fill capacity	gal	2.904
25	Oil carry over	ppm	3
26	Reference conditions - ambient & altitude	°F/ ft	113 and 3280
27	Discharge oil temperature	°F	Minimum: Above PDP at given pr. & 90% RH
		°F	Maximum: Ambient + 104.4
28	Maximum allowable air temperature at outlet	°F	Less than Ambient+27
29	Noise level of the compressor	dB (A)	69+3
30	Air outlet port size	inch	1 1/4" NPT Thread
31	Overall dimensions of the unit, L x B x H	inch	36.76 x 45.45 x 63.24
32	Overall dimensions with packing, L x B x H	inch	42.5 x 47.2 x 69.9
33	Package nett. weight (Dry condition)	lbs	1259
34	Package gross weight with packing	lbs	1364
35	Reference standard for FAD and SPC	-	ISO 1217- Annexure 'C '
36	Reference standard for noise level	-	ISO 2151, Second Edition
37	Reference standard for air purity	-	ISO 8573-1

Note:-

Prepared By	ARAVINTH N	Approved By	SUBRAMANIAN K
-------------	------------	-------------	---------------

All data and information in this sheet are confidential and property of ELGI EQUIPMENTS LIMITED

This is system generated document and hence signature is not required