



Piston Technical Data Sheet

QP-5

HP	5	cfm@175 psi	17.2
Low Pressure_Bor	4"	Pump Speed	680
High Pressure_Bor	2.25"		
Stroke	3"	80 Gal V	80 Gal H
Max Working Pres	175	Dims (LxWxH)	37x24x74 70X23X74
Inlet Size	1" NPT	Weight	680 660
Air Outlet Size	3/4" BALL VALVE		
Min/Max RPM	400-1060 RPM		
Pump Life	50,000 HRS	Tank Pressure	200 psi
Duty Cycle	100%	Tank Fill Time	7.4 min
Lubrication	Quin-Cip		
Sump Capacity	1.93 qts. (1.83 lit.)	Standard Warranty	Factory - 12 months parts / 12
Noise _dB(A)	73.6 ± 3	Extended Warr	3-Year Pump/ 2-Year Packa
Min operating_Temp	0 deg F	EWK part number	EWK-6
Max operating_Temp	104 deg F	EWK Contents	1 Air Filter, 3 Oil Filters, 6 qts Quin-Cip D

\*Duplex unit owners must purchase two (2) EWK kits  
 \*Engine-driven unit extended warranty is on air compressor only, "less engine". See engine manufacturer for warranty coverage.

Voltage:	120/1	230/1	200/3	230/3	460/3	575/3
Amp Draw:	-	28	17.5	15.2	7.6	6.1

\*Applicable data doubled for Duplex models