



20 Gallon Cast Iron - Oil Lubricated - Belt Drive

FEATURES & BENEFITS

- Cast iron, V-twin cylinder, oil lubricated pump features
 - One-piece cast iron crankcase
 - Thermally stable cast iron cylinder body
 - Aluminum head & machined cast iron valve plate
 - Automotive style ball bearings
 - Durable stainless steel reed valves
 - Oil level sight glass
 - Easily accessible oil fill
 - 10" cast iron balanced flywheel
- Heavy duty induction motor for maximum performance and efficiency
- 155 PSI max pressure for optimum tool performance
- 20 gallon ASME* portable tank equipped with pneumatic tires for maximum portability
- Dual voltage motor is wired for standard 120 volt outlet, and may also be converted for 240 volt application
- Equipped with quick-set regulator, tank and tool pressure gauges, quick connect air outlet and on/off switch
- Supported by our Toll Free Customer Help Line



MODEL SPECIFICATIONS

Tank Size:	20 Gallon ASME*
Maximum Pressure:	155 PSI
CFM @ 40 PSI:	6.2
CFM @ 90 PSI:	5.3
Voltage:	120/240 Volt
Running HP:	1.6
Certifications:	UL & CSA
Limited Warranty:	2 Year Pump 1 Year All Other Parts

Dimensions: 25" x 24.5" x 49 • Weight: 159 lbs. • UPC: 8 46212 02428 7 • Pallet Qty: 4 • Truckload Qty: 192 (53' trailer)

*ASME - American Society of Mechanical Engineers Product style and configuration may vary.

MODEL: DXCMLA1682066

©2014 SANDOR MFG. ALL RIGHTS RESERVED.