



# 60 Gallon - Cast Iron Oil Lubricated Belt Drive Air Compressor

## FEATURES & BENEFITS

- 175 PSI max pressure for optimum tool performance
  - Over 2X longer air tool run time\*\*
  - 30% higher PSI\*\*
- Cast iron, twin cylinder, oil lubricated pump features
  - Poly-v pulley and drive belt provides smooth operation with less vibration
  - High efficiency aluminum flywheel provides maximum air flow and lower start-up amps due to less starting inertia
  - Aluminum head and valve plate to maximize heat dissipation
  - High grade stainless steel valves
  - Superior O-Ring seals to eliminate oil leaks
- Heavy duty, 208-230 spread volt induction motor designed to operate at both 208 and 230 volt applications
- Large capacity, 60 gallon ASME\* air receiver provides more air for longer run times on air tools such as ratchets, impacts, spray guns, hammers, etc
- Equipped with pressure gauge and on/off switch
- Tie down holes on platform sides to secure unit when transporting
- Supported by our Toll Free Customer Help Line



## MODEL SPECIFICATIONS

Tank Size:	60 Gallon ASME*
Maximum Pressure:	175 PSI
CFM @ 40 PSI:	13.4
CFM @ 90 PSI:	11.5
Voltage:	208-230 Spread Volt
Running HP:	3.7
Certifications:	CSA C-US*
Limited Warranty:	2 Year Pump 1 Year All Other Parts
Model:	DXCM602
UPC:	8 46212 08367 3
.com Model:	DXCM602.com
UPC:	8 46212 08375 8
Dimensions:	40" x 48" x 80"
Weight:	278 lbs

Dimensions: 24" x 24" x 78" • Weight: 237 lbs. • Pallet Qty: 1 • Truckload Qty: 104 (53' trailer)

\*ASME - American Society of Mechanical Engineers • Certified to UL1450 and CSA22.2 No 68 \*\* vs other 60 gallon 135 PSI compressors

Product style and configuration may vary.

