




288 CFM – 575 CFM Premium Industrial Refrigerated Air Dryers



1 Micron Active Coalescing Filter



Auto Drain system - eliminates the need for daily maintenance



- Purifies compressed air by chilling to condense moisture
- High Refrigerant Safety
- Condensate is drained carrying oil and dirt particles away from the air
- Outlet air baffle heater - prevents condensation on outlet air piping
- Heavy duty steel cabinet
- Trouble free operation refrigerated air inlet inner cooler for high temp cooling
- Side mounted condenser & Fan Motor
- Environmentally friendly 134A refrigerant
- Pre-Plumbed
- 5 Micron Pre-Filter
- Quick, Easy to Remove Cabinet Door for Easy Servicing - No Screws!

	EDRCF230288	EDRCF460288	EDRCF230575	EDRCF460575
CFM	288	288	575	575
Pipe Size	2"	2"	3"	3"
Voltage 60hz	230 V - 3 Phase	460 V - 3 Phase	230 V - 3 Phase	460 V - 3 Phase
Amperage	14	14	10	10
Filteration	Built in Coalscing	Built in Coalscing	Built in Coalscing	Built in Coalscing
Dew Point (F)	37-50	37-50	37-50	37-50
Max Working PSI	230	230	230	230
Max Inlet Temp (F)	150	150	150	150
Refrigerant Type	134A	134A	134A	134A
Max Ambient Temp	120	120	120	120
Drain Type	Automatic	Automatic	Automatic	Automatic
Dims: LXWXH	32" x 42" x 54"	32" x 42" x 54"	27" x 31" x 55"	27" x 31" x 55"
Weight (LBS)	480	480	500	500

1000 Cass Drive
 Englewood, OH 45315
 Toll Free: 866-294-4153
 Fax: 937-540-1157

5 Yr- Limited warranty on heat exchanger
 2 YR- Limited warranty on all other parts

www.emaxcompressor.com

