




## 30 CFM – 144 CFM Premium Industrial Refrigerated Air Dryers



• 1 Micron Active Coalescing Filter



• Auto Drain system - eliminates the need for daily maintenance



- Purifies compressed air by chilling to condense moisture
- High Refrigerant Safety
- Condensate is drained carrying oil and dirt particles away from the air
- Outlet air baffle heater - prevents condensation on outlet air piping
- Heavy duty steel cabinet
- Trouble free operation refrigerated air inlet inner cooler for high temp cooling
- Side mounted condenser & Fan Motor
- Environmentally friendly 134A refrigerant
- Pre-Plumbed
- 5 Micron Pre-Filter
- Quick, Easy to Remove Cabinet Door for Easy Servicing - No Screws!

	EDRCF1150030	EDRCF1150058	EDRCF1150115	EDRCF1150144
<b>CFM</b>	30	58	115	144
<b>Pipe Size</b>	1/2"	3/4"	1 1/2"	1 1/2"
<b>Voltage 60hz</b>	115	115	115	115
<b>Amperage</b>	4	7.2	11	14
<b>Filteration</b>	Built in Coalscing	Built in Coalscing	Built in Coalscing	Built in Coalscing
<b>Dew Point (F)</b>	37-50	37-50	37-50	37-50
<b>Max Working PSI</b>	230	230	230	230
<b>Max Inlet Temp (F)</b>	140	140	140	150
<b>Refrigerant Type</b>	134A	134A	134A	134A
<b>Max Ambient Temp</b>	122	122	122	120
<b>Drain Type</b>	Automatic	Automatic	Automatic	Automatic
<b>Dims: LXWXH</b>	16" x 18" x 24"	24" x 19" x 30"	26" x 23" x 36"	26" x 23" x 36"
<b>Weight ( LBS)</b>	110	120	180	180

1000 Cass Drive  
 Englewood, OH 45315  
 Toll Free: 866-294-4153  
 Fax: 937-540-1157

5 Yr- Limited warranty on heat exchanger  
 2 YR- Limited warranty on all other parts

[www.emaxcompressor.com](http://www.emaxcompressor.com)

