



Americas

Electric-Driven Two-Stage Air Compressors

Model	Tank (gal)	Max Pressure (psig)	Nominal Power (hp)	Flow at Max Pressure (cfm)	Base Length (in)	Base Width (in)	Base Height (in)	Weight (lbs)	NPT Outlet (in)	Voltage/Engine
2340L5-V	60 vertical	175	5	14.0	48	40	76	435	1/2	230 - 1-60 / 200, 230, 460, 575 - 3 - 60
2340N5-V	80 vertical	175	5	14.0	48	40	76	505	1/2	230 - 1-60 / 200, 230, 460, 575 - 3 - 60
2475N5-V	80 vertical	175	5	16.8	48	40	76	597	3/4	230 - 1-60 / 200, 230, 460, 575 - 3 - 60
2475N5-P	80 vertical	175	5	16.8	48	40	76	597	3/4	230 - 1-60 / 200, 230, 460, 575 - 3 - 60
2475N7.5-V	80 vertical	175	7.5	24.0	48	40	76	611	3/4	230 - 1-60 / 200, 230, 460, 575 - 3 - 60
2475N7.5-P	80 vertical	175	7.5	24.0	48	40	76	611	3/4	230 - 1-60 / 200, 230, 460, 575 - 3 - 60
2545E10-V	120 horizontal	175	10	35.0	83	36	65	920	3/4	200, 230, 460, 575 - 3 - 60
2545E10-VP	120 horizontal	175	10	35.0	83	36	65	1104	3/4	200, 230, 460, 575 - 3 - 60
2545E10-P	120 horizontal	175	10	35.0	83	36	65	1104	3/4	200, 230, 460, 575 - 3 - 60
2545K10-V	120 vertical	175	10	35.0	51	46	83	920	1	200, 230, 460, 575 - 3 - 60
2545K10-VP	120 vertical	175	10	35.0	51	46	83	1104	1	200, 230, 460, 575 - 3 - 60
2545K10-P	120 vertical	175	10	35.0	51	46	83	1104	1	200, 230, 460, 575 - 3 - 60
7100E15-V	120 horizontal	175	15	50.0	83	36	65	1239	3/4	200, 230, 460, 575 - 3 - 60
7100E15-VP	120 horizontal	175	15	50.0	83	36	65	1297	3/4	200, 230, 460, 575 - 3 - 60
7100E15-P	120 horizontal	175	15	50.0	83	36	65	1297	3/4	200, 230, 460, 575 - 3 - 60
15TE15-P	120 horizontal	175	15	53.0	88	46	65	1597	3/4	200, 230, 460 - 3 - 60
15TE20-P	120 horizontal	175	20	72.0	88	46	65	1597	3/4	200, 230, 460 - 3 - 60