



COMPRESSOR PLATFORM LAYOUT

PART NUMBER	DESCRIPTION	A	B	C (DIA.)	D	E	F	G	H	J
S040-0352	PUMP; OIL LUBRICATED, BELT DRIVE, CAST IRON, IN-LINE TWIN CYLINDER	5.75"	5.88"	Ø.35"	1.47"	12.0"				
040-0348	PUMP; OIL LUBRICATED, BELT DRIVE, CAST IRON, 3-CYLINDER HIGH FLOW	5.20"	8.44"	Ø.35"	2.38"	12.0"				
S040-0354	PUMP; OIL LUBRICATED, BELT DRIVE, CAST IRON, IN-LINE TWIN CYLINDER	5.80"	5.88"	Ø.35"	1.47"	12.0"				
040-0386	PUMP; OIL LUBRICATED, BELT DRIVE, CAST IRON, V- TWIN CYLINDER	3.54"	6.75"	Ø.35"	1.87"	10.5"				
040-0429	PUMP; OIL LUBRICATED, BELT DRIVE, ALUMINUM WITH CAST IRON, IN-LINE TWIN CYLINDER	5.75"	5.88"	Ø.37"	1.47"	12.0"				
040-0430	PUMP; OIL LUBRICATED, BELT DRIVE, ALUMINUM WITH CAST IRON, IN-LINE TWIN CYLINDER	5.75"	5.88"	Ø.37"	1.47"	12.0"				
040-0431	PUMP; TWO-STAGE, OIL LUBRICATED, BELT DRIVE, CAST IRON, IN-LINE TWIN CYLINDER	6.25"	9.0"	Ø.41"	2.75"	18.0"				
160-0264	MOTOR; 1.9 RHP 115/230 VOLT, 15/7.5 AMP, 60 HERTZ, 1 PHASE, 3450 RPM						3.00"	4.88"	.34 x 1.22"	2.75"
160-0266	MOTOR; 3.1 RHP SPL, 240 VOLT, 15 AMP, 60 HERTZ, 1 PHASE, 3450 RPM						4.87"	3.00"	Ø.31"	2.62"
S160-0325	MOTOR; 4.7 RHP, 230 VOLT, 17.5 AMP, 60 HERTZ, 1 PHASE, 3450 RPM						4.00"	5.50"	Ø.31"	2.00"
S160-0337	MOTOR; 5 RHP, 230 VOLT, 22 AMP, 60 HERTZ, 1 PHASE, 3450 RPM						4.00"	5.50"	Ø.31"	2.00"
160-0291	MOTOR; 5 RHP, 230 VOLT, 24 AMP, 60 HERTZ, 1 PHASE, 4-POLE, 1725 RPM, BALDOR						4.50"	7.50"	.41 x 2.50"	2.00"
160-0029	MOTOR; 5 RHP, 230/460 VOLT, 13/6.5 AMP, 60 HERTZ, 3 PHASE, 1745 RPM						5.50"	7.50"	.41 x 2.50"	2.75"
160-0258	MOTOR; 7.5 RHP, 230 VOLT, 29 AMP, 60 HERTZ, 1 PHASE, 1745 RPM						7.75"	9.00"	.41 x 2.50"	2.75"
160-0026	MOTOR; 10 RHP, 230/460 VOLT, 27/13.5 AMP, 60 HERTZ, 3 PHASE, 1745 RPM						5.50"	7.50"	.41 x 2.50"	2.75"