



ROLAIR STANDARD FEATURES

PUMP: Two-Stage, Cast-Iron Cylinders, Aluminum Head and Crankcase for Faster Heat Dissipation, Ball Bearings, Splash-Lubricated, Bearing Inserts on Connecting Rods, High-Efficiency Reed Valves, Low RPM's to Ensure Long Life and Trouble-Free Performance. **For Pump Specifications See Reverse Side**

TANK : Horizontal or Vertical
60, 80 or 120 Gallon - ASME
(Base-Mount Units Also Available)

APPROXIMATE SHIPPING WEIGHT:
465 lb. - 60 Gallon Models
530 lb. - 80 Gallon Models
700 lb. - 120 Gallon Models

MOTOR: Open Drip-Proof
208/230 Volt – 60 Hz - 1800 RPM – 1 Phase
208/230/460 Volt–60 Hz-1800 RPM – 3 Phase
S-1 Rated for Continuous Duty

STANDARD EQUIPMENT

- Pressure Switch - Start/Stop Operation 145-175 PSI Settings, On/Off Switch
- Automatic Unloading Device for Loadless Starts
- Heavy-Duty Brass Shut-Off Valve
- Pressure Gauge - 0-300 PSI in 5 lb. Graduations
- Safety Relief Valve - ASME Approved
- V-Belt Drive
- Intake Filter/Silencer with Replaceable Element
- Totally Enclosed Steel Belt Guard

OPTIONAL EQUIPMENT

Magnetic Starter, Automatic Tank Drain, Low-Oil Shutdown, Level-Rite Mounts, Vibration Pads, 208V Motor, Dual Controls, Head Unloader, Air-Cooled Aftercooler, Refrigerant Air Dryer,

MODEL PMP22K30CH



K30

SPECIFICATIONS

NO. OF CYLINDERS	CYLINDERS BORE & STROKE (inches)	OIL CAPACITY (oz.)	FWHL DIAMETER (inches)	DRY WEIGHT (lb.)	MAXIMUM PRESSURE
2	4.13 & 2.05 x 3.31	47	15.16	85	200 PSI

PERFORMANCE

HP	DISCHARGE PRESSURE	CFM DISPLACED @ 175 PSI	CFM DELIVERED @ 175 PSI	PUMP RPM
7.5	175 PSI	32.3	24.8	1250