Compressed Air Cleaning Filter Series

For Water, Solid/Oil Separation and Deodorization

Modular connection, Space-saving design, Labor-saving in piping! (AMGIC, AFFIC, AMCIC, AMDIC, AMDIC) Uses the same spacer as the F.R.L. combination AC series. Modular connection example Possible to make a modular connection with products such as AR series regulator. Spacer Note) AMH + AMF AMH + AME + AMF Note) Spacer with bracket cannot be mounted. Use the attached bracket. * The C type is only suitable for modular connection. **Options added** (AMGC, AFFC, AMC, AMDC) AMHC, AMEC, AMFC) Compact, Lightweight (AMEIC, AMFIC) Differential pressure switch Height and mass reduced by up to **40**% Addition: **5** types Conventional 1.6 MPa specifications New Fluororubber specifications With differential pressure switch (125 VAC, 30 VDC) With differential pressure switch (30 VDC) Degreasing wash, white vaseline specifications Water Separation Water Separator/AMG Solid/Oil Separation Main Line Filter/AFF Mist Separator/AM Micro Mist Separator/AMD Micro Mist Separator with Pre-filter/AMH Super Mist Separator/AME Deodorization Odor Removal Filter/AMF



Series AM / AFF



AMD150C to 550C AMD650 to 1000



1000

40,000

100(4B), 150(6B) flange

Series AM / AFF

Dust filtration, Oil mist separation

Micro Mist Separator with Pre-filter

Built-in 0.3 µm pre-filter The AM + AMD element have been integrated to achieve a space-saving design. Nominal filtration rating: 0.01 µm [Filtration efficiency: 99.9%] Oil mist density at outlet: Max. 0.1 mg/m³ (ANR)

[≈0.08 ppm]



AMH150C to 550C AMH650/850

Dust filtration, Oil mist adsorption

Super Mist Separator

Color change indicates when element is saturated.

0

Nominal filtration rating: 0.01 µm [Filtration efficiency: 99.9%] Oil mist density at outlet:

Max. 0.01 mg/m³ (ANR) [\approx 0.008 ppm] Cleanliness at outlet: Not more than 35 particles of size 0.3 μ m or larger/10 ℓ (100 particles or loss/tt3)



(100 particles or less/ft³) AME150C to 550C

Deodorization

Odor Removal Filter

Nominal filtration rating: 0.01 μm [Filtration efficiency: 99.9%] Oil mist density at outlet: Max. 0.004 mg/m³ (ANR) [≈0.0032 ppm]



AMF150C to 550C

AMF650 to 1000

Mo	odel	Flow capacity ℓ /min (ANR) Max. flow capacity at 0.7 MPa inlet pressure	Port size	Note
	150C	200	1/8, 1/4	
	250C	500	1/4, 3/8	
	350C	1,000	3/8, 1/2	
АМН	450C	2,000	1/2, 3/4	Piping support
	550C	3,700	3/4, 1	туре
	650	6,000	1, 1 ^{1/} 2	
	850	12,000	1 ¹ /2, 2	
	150C	200		
	250C	500	1/4, 3/8	
	350C	1,000	3/8, 1/2	D
AME	450C	2,000	1/2, 3/4	Piping support type
	550C	3,700	3/4, 1	type
	650	6,000	1, 1 ^{1/} 2	
	850	12,000	1 ¹ /2, 2	
	150C	200	1/8, 1/4	
	250C	500	1/4, 3/8	
	350C	1,000	3/8, 1/2	
	450C	2,000	1/2, 3/4	
	550C	3,700	3/4, 1	Piping
	650	6,000	1, 1 ^{1/} 2	type
	850	12,000	1 ¹ /2, 2	
	801	8,000	50(2B) flange	
	901	24,000	50(2B), 80(3B) 100(4B) flange	
	800	8,000	50(2B) flange	
	900	24,000	50(2B), 80(3B) 100(4B) flange	Free
	1000	40,000	100(4B), 150(6B) flange	type



Compressed Air Cleaning Filter Series



		Series	removal rate	filtration rating	at outlet	Smell	Page
Water Separator	Water Separator Eliminates water droplets in the compressed air.	Series AMG	99%	_	_	_	P.2
	• Main Line Filter Eliminates impurities such as oil and foreign matter, etc. in compressed air.	Series AFF		3 μm (Filtration efficiency: 99%)	_		P.10
tor	 Mist Separator Eliminates oil mist in compressed air or rust sized 0.3 μm or more, and foreign matter such as carbon. 	Series AM		0.3 μm (Filtration efficiency: 99.9%)	1 mg/m³ (ANR) (≈0.8 ppm) (after oil saturation)	_	P.18
olid/Oil Separa	• Micro Mist Separator Eliminates foreign matter sized 0.01 µm or more, or oil particles in an aerosol state.	Series AMD		0.01 µm (Filtration efficiency: 99.9%)	0.1 mg/m ³ (ANR)		P.26
ŭ	Micro Mist Separator with Pre-filter Oil separator, which incorporates pre-filter (equivalent to the AM series) into micro mist separator.	Series AMH		0.3 + 0.01 μm (Filtration efficiency: 99.9%)	(after oil saturation)		P.36
	• Super Mist Separator Captures foreign matter sized 0.01 µm or more and adsorbs oil particles in an aerosol state.	Series AME		0.01 μm (Filtration	0.01 mg/m³ (ANR) (≈0.008 ppm)	Reduces oil smell.	P.44
Deodorizer	Odor Removal Filter Eliminates odor from compressed air.	Series AMF		efficiency: 99.9%)	0.004 mg/m³ (ANR) (≈0.0032 ppm)	Deodorizes oil smell.	P.52
I	Modular Connection Examples						P.61
I	How to Order Bowl Assembly						P.63
	Seal m For me With di (125 V/	aterial: Fluororu dium air pressu fferential pressur AC, 30 VDC)	lbber ● IN-C re ● Drai e switch (wit	DUT reversal directi in guide 1/4 female th indicator) • With (30	on • Degreasing threaded white vaseli • With elemer h differential pressure swi VDC)	wash, ne nt service indicator itch (with indicator)	Refer to "How to Order" of respective models.
1	With d Possibl by mon Auto d specifi Drain p With IN Flange	fferential pressu e to control produ- itoring the clogge rain type, drain cations iping is possible I I-OUT flange piping connection	ure gauge uct's service d element. guide by auto drain n is possible.	life U	White vaseline specifica Jsing white vaseline for lu With differential pressur N-OUT flange Flange piping connection a element confirmation are p With differential pressur with indicator)* Allows visual confirmation pressure which indicates t The built-in contact enable	tions* bricant. e gauge, and clogged possible. e switch of differential he element life. es remote control.	P.67
∗ Ар	plicable only to the AFF37B, 75B, AMD650	and 850.		0 (
:	Special Specifications Usable	inside a clean roo	om.	Copper-free Eliminates th fluoric resin,	e, Fluorine-free he effects on a color CRT etc.	by copper ion or	P.67
I	Related Products Auto D	ain Valve, Motor	Operated A	uto Drain, Heavy Du	uty Auto Drain, Differenti	al Pressure Gauge	P.73
9	Specific Product Precautions						Back page 3
I	Discontinued Model and Equivalen	t Model					Back page 7

SMC

Water Separator Series AMG

Can remove water droplets in compressed air. Use this product in cases where "water must be avoided, but not so dry as when an air dryer is used".

Through the adoption of an element that is exclusively used for removing water droplets and the ample housing interior space, a 99%* water removal rate** has been achieved.

▲ Caution

Water separator can remove water droplets, but it cannot remove moisture.

* Condition of inlet air

- Pressure: 0.7 MPa
- Temperature: 25°C
- Relative humidity: 100%
- Liquid water content (Water droplet

content): 15 g/m³ (ANR)

Compressed air flow: Rated flow of each model

** Water removal rate (%) = Removed water (Water droplet) (g) x 100

Inflowed water (Water droplet) (g)

Modular connection is possible with AMG150C to 550C. (For details, refer to page 61.)





AMG150C to 550C

AMG650/850

Symbol AMG



Made to Order (For details, refer to page 67.)

Model

Model	AMG150C	AMG250C	AMG350C	AMG450C	AMG550C	AMG650	AMG850
Note) Rated flow (ℓ/min (ANR))	300	750	1500	2200	3700	6000	12000
Port size	1⁄8, 1⁄4	1/4, 3/8	3⁄8, 1⁄2	1/2, 3/4	3⁄4, 1	1, 11⁄2	1 ¹ / ₂ , 2
Mass (kg)	0.38	0.55	0.9	1.4	2.1	4.2	10.5

Note) Max. flow at 0.7 MPa.



Max. flow varies depending on the operating pressure. Refer to "Flow Characteristics" (page 5) and "Maximum Air flow" (page 6).

Specifications

Fluid	Compressed air
Max. operating pressure	1.0 MPa
Min. operating pressure*	0.05 MPa
Proof pressure	1.5 MPa
Ambient and fluid temperature	5 to 60°C
Water removal rate	99%
Element life	2 years or when pressure drop reached 0.1 MPa

* With auto drain: 0.1 MPa (N.O. type) or 0.15 MPa (N.C. type)

Accessorv

Applicable model	AMG150C	AMG250C	AMG350C	AMG450C	AMG550C	AMG650	AMG850
Bracket assembly (with 2 mounting screws)	AM-BM101	AM-BM102	AM-BM103	AM-BM104	AM-BM105	BM56	BM57

🗥 Caution

- Be sure to read this before handling.
- L
- Refer to back pages 1 and 2 for Safety Instructions, "Precautions for I L Handling Pneumatic Devices" (M-03-E3A) for Common Precautions, and back pages 3 through to 7 for Specific Product Precautions.

Series AMG



• •	iui	ai options cam	101 00 30100100	u.		
((i.e.	Combinations	such as C-FV	, D-FHV	are not	possib

(i.e. Combinations such	as C-F∖	′, D-FH\	/ are no	t possib	le.)
Symbol	F	Н	R	V	1
Auto drain specifications Nil	0	0	0	0	
С	\bigtriangleup		0		
D	\bigtriangleup	\bigtriangleup	0		
J	\bigcirc	\bigcirc	\odot	0	

Options

Symbol F: Rubber material: Fluororubber Fluororubber is used for the parts such as O-ring and gasket. Symbol R: IN-OUT reversal direction

Air flow in the separator is changed to right to left. (Air flow direction of the standard: Left to right.)

Symbol H: For medium air pressure (1.6 MPa)

Can be used up to 1.6 MPa at maximum.

Symbol V: Degreasing wash, white vaseline

Body/housing is degreasing washed. The lubrication grease for O-ring and gasket is changed to white vaseline.





Water Separator Series AMG



*3 Body size 850 is equipped with a ball valve (Rc3/8 female threaded). Mount a piping adapter IDF-AP609 (page 62) to the ball valve if NPT3/8 female threaded is required.

Note) Refer to "How to Order Bowl Assembly" on page 63.

Auto Drain Specifications/Option Combinations												
Auto droip oposifi	actiona/Ontion		Auto drain specifications	Op	tion	Applicab	le model					
Auto drain specin	cations/Option		D	J	R	AMG650	AMG850					
Auto drain specifications	N.O. auto drain	D			0	0	0					
	Drain guide 1/4	J			0	0						
Option	IN-OUT reversal direction	R	O	0		0	0					

Series AMG

Flow Characteristics

Note) Compressed air over max. flow line in the table below may not meet the specifications of the product. It may cause damage to the element.





AMG550C



AMG350C **AMG650** Max. flow line 0.5Mpa 0.01 0.002 0.3Mpa 0.5Mpa -O.7Mpa 0.3Mp Bressure drop (MPa) 0.005 0.0025 Pressure drop (MPa) 100'0 2000'0 2000'0 0.0015 Max. flow line 0 0 0 400 800 1200 1600 2000 0 1500 3000 4500 6000 7500 Air flow rate (*ℓ*/min (ANR)) Air flow rate (*ℓ*/min (ANR))

Construction



Replacement Parts

1

2

No De			Applicable				Model			
NO. DE	escription	Material	model	AMG150C	AMG250C	AMG350C	AMG450C	AMG550C	AMG650	AMG850
A EI	Element	Resin,	Except option F	AMG-EL150	AMG-EL250	AMG-EL350	AMG-EL450	AMG-EL550	AMG-EL650	AMG-EL850
4 as	assembly	others	For option F	AMG-EL150-F	AMG-EL250-F	AMG-EL350-F	AMG-EL450-F	AMG-EL550-F	_	_

* Element assembly: With gasket (1 pc.) and O-ring (1 pc.)

* Refer to back page 6 for replacement of auto drain.

* Element assemblies for Made to Order (X12, X15, X20, X26) are same as those for standard (see the above table).

Maximum Air Flow



Model Selection

Select a model in accordance with the following procedure taking the inlet pressure and the max. air flow rate into consideration. (Example) Inlet pressure: 0.6 MPa

Max. air flow rate: 5 m3/min (ANR)

- 1. Obtain the intersecting point A of inlet pressure and max. air flow rate in the graph.
- 2. The AMG650 is obtained when the max. flow line is above the interecting point A in the graph.



Note) Make sure to select a model that has the max. flow line above the obtained intersecting point. With a model that has the max. flow line below the obtained intersecting point, the flow rate will be exceeded, thus leading to a problem such as being unable to satisfy the specifications.



Series AMG

Dimensions

AMG150C to 550C







Combination of D: With auto drain (N.O.) and H: For medium air pressure



Option J: Drain guide 1/4 female threaded



																							(mm)
Madal	Dort oizo	•	Р	6	D	E	E	~						Brack	ket re	lated	dime	nsior	S				
woder	Port size	A	Р	C	U	E	F	G	Н	I	J	κ	Т	U	L	М	۷	Ν	0	Ρ	Q	R	S
AMG150C	1/8, 1/4	158	10	99	63	20	63	10	173	56	20	5	6	6	12	6	10	35	54	70	26	4.5	1.6
AMG250C	1/4, 3/8	172	14	113	76	20	76	10	190	66	24	8	6	6	12	6	10	40	66	80	28	5	2
AMG350C	3/8, 1/2	204	18	145	90	20	90	10	222	80	28	8	7	7	14	7	12	50	80	95	34	5	2.3
AMG450C	1/2, 3/4	225	20	166	106	20	106	10	246	90	31	10	9	9	18	9	15	55	88	111	50	9	3.2
AMG550C	3/4, 1	259	24	200	122	20	122	15	278	100	33	10	9	9	18	9	15	65	102	126	60	10	3.2

Dimensions

AMG650





Option









Series AMG

Dimensions

AMG850







Main Line Filter Series AFF

Can remove impurities such as oil, water and foreign matter in compressed air and can improve the function of a dryer in the downstream, extend the life of precision filter, and prevent trouble with the equipment.

Modular connection is possible with AFF2C to 22C. (For details, refer to page 61.)

(For details, relef to page 61.)





AFF37B/75B

AFF75A to 220A



Made to Order (For details, refer to page 67.)

▲ Caution

Be sure to read this before I handling.
Refer to back pages 1 and 2 I for Safety Instructions, "Pre-I cautions for Handling Pneu-I matic Devices" (M-03-E3A) for I Common Precautions, and I back pages 3 through to 7 for I

Specific Product Precautions.

Model

mouci											
Model	AFF2C	AFF4C	AFF8C	AFF11C	AFF22C	AFF37B	AFF75B	AFF75A	AFF125A	AFF150A	AFF220A
Rated flow Note) (ℓ/min (ANR))	300	750	1500	2200	3700	6000	12000	12000	22000	28000	42000
Port size	1/8, 1/4	1/4, 3/8	3/8, 1/2	1/2, 3/4	3⁄4,1	1,11⁄2	1 ¹ ⁄2, 2	50(2B)	80(3B)	100(4B)	100(4B)
								J	13 IUK I	FF hang	e
Mass (kg)	0.38	0.55	0.9	1.4	2.1	4.2	10.5	50	52	72	87



Note) Max. flow at 0.7 MPa. Max. flow varies depending on the operating pressure.

Refer to "Flow Characteristics" (page 13) and "Maximum Air Flow" below.

Specifications

Fluid	Compressed air
Max. operating pressure	1.0 MPa
Min. operating pressure*	0.05 MPa
Proof pressure	1.5 MPa
Ambient and fluid temperature	5 to 60°C
Nominal filtration rating	3 μm (Filtration efficiency: 99%)
Element life	2 years (1 year for A type) or when pressure drop reached 0.1 MPa

* With auto drain: 0.1 MPa (N.O. type) or 0.15 MPa (N.C. type)

Accessory/For AFF2C to 22C, AFF37B/75B

Applicable model	AFF2C	AFF4C	AFF8C	AFF11C	AFF22C	AFF37B	AFF75B
Bracket assembly (with 2 mounting screws)	AM-BM101	AM-BM102	AM-BM103	AM-BM104	AM-BM105	BM56	BM57

Accessory/For AFF75A to 220A

Applicable model	AFF75A	AFF125A	AFF150A	AFF220A									
Auto drain (2 pcs. each)		AD402-03-2											
Pressure gauge (2 pcs. each)		G46-15-02											
Companion flange (2 pcs. each)	50(2B)JIS 10K FF flange	80(3B)JIS 10K FF flange	100(4B)JIS 1	0K FF flange									
Anchor bolt (3 pcs. each)	AI-2S												

Model Selection

Select a model in accordance with the following procedure taking the inlet pressure and the max. air flow rate into consideration. (Example) Inlet pressure: 0.6 MPa

Max. air flow rate: 5 m³/min (ANR)

- 1. Obtain the intersecting point A of inlet pressure and max. air flow rate in the graph.
- The AFF37B is obtained when the max. flow line is above the intersecting point A in the graph.
 - Note) Make sure to select a model that has the max. flow line above the obtained intersecting point. With a model that has the max. flow line below the obtained intersecting point, the flow rate will be exceeded, thus leading to a problem such as being unable to satisfy the specifications.

Maximum Air Flow





Series AFF

How to Order



Auto Drain Specifications/Option Combinations

0

 \bigcirc , \triangle : Plural options cannot be selected.

1

(i.e. Combinations such as C-FV, D-FHV, J-ST are not possible.)

Symbol	F	Н	R	S	U	Т	V
Auto drain specifications Nil	0	0	0	0	0	0	0
С	\triangle		0	0	0	0	\triangle
D	\triangle	\triangle	0	0	0	0	\triangle
J	0	0	0	Ó	Ó	0	0

Made to Order

("How to Order" and the applicable models are different from those shown on this page. Be sure to refer to "Made to Order".)

Symbol	Description	Page for details
Nil	—	—
X6	With differential pressure gauge (GD40-2-01)	P.68
X15	With IN-OUT flange	P.69
X17	With differential pressure gauge (GD40-2-01) and IN-OUT flange	P.69
X26	N.C., N.O. auto drain, drain piping type	P.70

• Option *3

Symbol	Description
Nil	—
F	Rubber material: Fluororubber
Н	For medium air pressure (1.6 MPa)
J	Drain guide 1/4 female threaded *4
R	IN-OUT reversal direction
S	With differential pressure switch (125 VAC, 30 VDC) *5, Note)
U	With differential pressure switch (30 V) *5, Note)
Т	With element service indicator
V	Degreasing wash,*6 white vaseline

*4 Drain piping and piping for a stop valve such as ball valve are required.

*5 Differential pressure gauge is included, (but not assembled).

*6 Only body/housing is degreasing washed. Note) Order "U" if conformity to the EU directive is required.

Auto drain *3

Symbol	Description
Nil	Drain cock (Without auto-drain)
С	N.C. auto drain
D	N.O. auto drain

*3 Refer to "Auto Drain Specifications/Option

Combinations".

Options

10





SMC

Symbol J: Drain	guide 1/4 female threaded
1/4 fer	Can be pipied to the drain exhaust port.
Symbol U: Wit switch (with in	h differential pressure dicator)
* The ra	Saturation of the separator can be observed visually or by an electrical signal. (Element life check) ated contact voltage is different S".
Max. contact cap Rated contact vo current): 30 V D0	bacity: 10 W DC bltage (max. operating C (0.33 A)
witch	0

11

Main Line Filter Series AFF

How to Order



Note) Refer to "How to Order Bowl Assembly" on page 63.

Auto Drain Specifications/Option Combinations

Auto Drain Specifi	cations/Option Combir	🔘 : Available 🛛 🔄 : Not available									
Auto droin	an a sifications (Ontion		Auto drain specifications		Option		Applicab	le model			
Auto drain	specifications/Option	D	J	R	Т	AFF37B	AFF75B				
Auto drain specifications	N.O. auto drain	D			0	0	0	0			
	Drain guide 1/4 J				0	0	O				
Option	IN-OUT reversal direction	R	0	0		0	0	0			
	With element service indicator	Τ	Ó	0	Ô		Ô	Ô			

AFF75A to 220A

100(4B) JIS 10K FF flange

Symbol

20

30

40



Anchor bolt

Series AFF

Flow Characteristics/Select the model taking the max. flow capacity into consideration. (Element oil saturation)

Note) Compressed air over max. flow line in the table below may not meet the specifications of the product. It may cause damage to the element.







Max. flow line

10

Air flow rate (m3/min (ANR))













C

AFF125A

0.01

0.008

Pressure drop (MPa) 90000 (MPa)

0.002



25

20

15







Construction



Replacement Parts

1

No. Description		Motorial	Applicable				Model			
No. Description	material	model	AFF2C	AFF4C	AFF8C	AFF11C	AFF22C	AFF37B	AFF75B	
	Element	Cotton paper,	Except option F	AFF-EL2B	AFF-EL4B	AFF-EL8B	AFF-EL11B	AFF-EL22B	AFF-EL37B	AFF-EL75B
4	assembly	others	For option F	AFF-EL2B-F	AFF-EL4B-F	AFF-EL8B-F	AFF-EL11B-F	AFF-EL22B-F	—	_

* Element assembly: With gasket (1 pc.) and O-ring (1 pc.)

* Refer to back page 6 for replacement of auto drain.

* Element assemblies for Made to Order (X6, X12, X15, X17, X20, X26, X37) are same as those for standard (see the above table).

AFF75A to 220A



Component Parts

No.	Description	Material	Note
1	Case	SGP-E, SS400	
2	Cover	SS400	

Replacement Parts

No.	Description		Qty.	Model										
		Material		AFF75A	AFF125A	AFF150A	AFF220A							
3	Element		1	EC700)-003N	EC800-003N	EC900-003N							
4	Seal	NBR	1	AL-	33S	AL-35S								

Series AFF

Dimensions

AFF2C to 22C







Combination of D: With auto drain (N.O.) and H: For medium air pressure



Option

J: Drain guide 1/4 female threaded



S, U: With differential pressure switch (with indicator)



T: With element service indicator



																										((mm)
Model	Port size	A	в	с	D	E	F	G					В	rack	ket re	elate	ed di	men	sions					Eler sen indicato dimer	ment vice r related nsions	Differ pres switch dimer	ential sure related nsions
									Н	I	J	K	Т	U	L	Μ	V	Ν	0	Ρ	Q	R	S	W	Χ	Y	Ζ
AFF2C	1/8, 1/4	158	10	99	63	20	63	10	173	56	20	5	6	6	12	6	10	35	54	70	26	4.5	1.6	24	37	32	41
AFF4C	1/4, 3/8	172	14	113	76	20	76	10	190	66	24	8	6	6	12	6	10	40	66	80	28	5	2	27	37	36	41
AFF8C	3/8, 1/2	204	18	145	90	20	90	10	222	80	28	8	7	7	14	7	12	50	80	95	34	5	2.3	32	37	42	41
AFF11C	1/2, 3/4	225	20	166	106	20	106	10	246	90	31	10	9	9	18	9	15	55	88	111	50	9	3.2	37	37	43	41
AFF22C	3/4, 1	259	24	200	122	20	122	15	278	100	33	10	9	9	18	9	15	65	102	126	60	10	3.2	39	37	51	41
15								-																			

SMC

Dimensions

AFF37B



160



Option









T: With element service indicator



Series AFF

Dimensions

AFF75B





Option

T: With element service indicator



AFF75A to 220A





SMC

ORIENTATION

								(mm)
Model	Port size	øA	В	С	D	Е	F	G
AFF75A	50(2B)JIS10K FF flange	200 (8B)	380	1125	935	505	265	184
AFF125A	80(3B)JIS10K FF flange	200 (8B)	380	1125	935	505	265	184
AFF150A	100(4B)JIS10K FF flange	250 (10B)	450	1178	980	540	265	236
AFF220A	100(4B)JIS10K FF flange	300 (12B)	500	1291	1070	670	325	282

Mist Separator Series AM

Can remove oil mist in compressed air and remove particles such as rust or carbon of more than 0.3 μ m.

Modular connection is possible with AM150C to 550C.

(For details, refer to page 61.)





AM150C to 550C

AM650/850

Symbol

Model

Model	AM150C	AM250C	AM350C	AM450C	AM550C	AM650	AM850
Note) Rated flow (@min (ANR))	300	750	1500	2200	3700	6000	12000
Port size	1/8, 1/4	1/4, 3/8	3⁄8, 1⁄2	1/2, 3/4	³ ⁄4, 1	1, 11⁄2	1 ¹ ⁄2, 2
Mass (kg)	0.38	0.55	0.9	1.4	2.1	4.2	10.5

Note) Max. flow at 0.7 MPa.

Max. flow varies depending on the operating pressure.

Refer to "Flow Characteristics" (page 21) and "Maximum Air Flow" (page 22). Note) Refer to "Made to Order" (page 67) for high flow type of AM850 or more.

Specifications

Fluid	Compressed air
Max. operating pressure	1.0 MPa
Min. operating pressure*	0.05 MPa
Proof pressure	1.5 MPa
Ambient and fluid temperature	5 to 60°C
Nominal filtration rating	0.3 μm (Filtration efficiency: 99.9%)
Oil mist density at outlet	Max. 1.0 mg/m³ (ANR) (≈0.8 ppm)*
Element life	2 years or when pressure drop reached 0.1 MPa

* With auto drain: 0.1 MPa (N.O. type) or 0.15 MPa (N.C. type)

* Oil mist density at 30 mg/m³ (ANR) blown out by compressor.

Accessory

\land Caution

Applicable model	AM150C	AM250C	AM350C	AM450C	AM550C	AM650	AM850
Bracket assembly (with 2 mounting screws)	AM-BM101	AM-BM102	AM-BM103	AM-BM104	AM-BM105	BM56	BM57



р В



Made to Order (For details, refer to page 67.)

Series AM

How to Order



Auto Drain Specifications/Option Combinations ○ : Available : Not available

 \bigcirc , \triangle : Plural options cannot be selected.

(i.e. Combinations such as C-FV, D-FHV, J-ST are not possible.)

(
Symbol	F	Н	R	S	U	Т	V								
Auto drain specifications Nil	O	0	O	0	0	0	0								
С	\triangle		0	0	0	0	\triangle								
D	\bigtriangleup	\bigtriangleup	0	0	0	0									
J	Ô	Ô	Ô	Ó	Ó	Ó	Ô								

Options



(1.6 MPa) Can be used up to 1.6 MPa at maximum. Symbol S: With differential pressure switch (with indicator) Saturation of the separator can be observed visually or by an electrical signal. (Element life check) * The rated contact voltage is different from "U".

Max. contact capacity: 10 VA AC, 10 W DC Rated contact voltage (max. operating current): 125 V AC (0.08 A), 30 V DC (0.33 A)



SMC



Made to Order

("How to Order" and the applicable models are different from those shown on this page. Be sure to refer to "Made to Order".)

Symbol	Description	Page for details
Nil	—	—
X6	With differential pressure gauge (GD40-2-01)	P.68
X15	With IN-OUT flange	P.69
X17	With differential pressure gauge (GD40-2-01) and IN-OUT flange	P.69
X26	N.C., N.O. auto drain, drain piping type	P.70

Option *3

Symbol	Description
Nil	—
F	Rubber material: Fluororubber
Н	For medium air pressure (1.6 MPa)
J	Drain guide 1/4 female threaded *4
R	IN-OUT reversal direction
S	With differential pressure switch (125 VAC, 30 VDC) *5, Note)
U	With differential pressure switch (30 VDC) *5, Note)
Т	Element service indicator
V	Degreasing wash,*6 white vaseline

*4 Drain piping and piping for a stop valve such as ball valve are required.

*5 Differential pressure gauge is included, (but not assembled).

*6 Only body/housing is degreasing washed.

Note) Order "U" if conformity to the EU directive is required.

Auto drain *3

Symbol	Description
Nil	Drain cock (Without auto drain)
С	N.C. auto drain
D	N.O. auto drain

*3 Refer to "Auto Drain Specifications/Option Combinations"



Mist Separator Series AM

How to Order



Note) Refer to "How to Order Bowl Assembly" on page 63.

Auto Drain Specifi	\bigcirc	🔘 : Available 🛛 🗌 : Not a							
	an a cifications (Ontion	Auto drain specifications		Option		Applicable model			
Auto drain	specifications/Option	D	J	R	Т	AM650	AM850		
Auto drain specifications	N.O. auto drain	D			0	0	0	0	
	Drain guide 1/4	J			0	0	0		
Option	IN-OUT reversal direction	R	0	0		0	0	0	
	With element service indicator	Т	0	Ô	Ô		Ô	Ô	

Series AM

Flow Characteristics (Element oil saturation)

Note) Compressed air over max. flow line in the table below may not meet the specifications of the product. It may cause damage to the element.





AM850





AM550C





AM650



Construction



Note) Refer to "How to Order Bowl Assembly" on page 63.

Component Parts

No.	Description	Material	Note
1	Body	Aluminum die-casted	Chrome treated
2	Housing	Aluminum die-casted*	Epoxy coating on inner surface
3	Sight glass	Tempered glass	_

* The AM850 is aluminum casted.

Replacement Parts

No.	Description	Motorial	Applicable				Model			
	Description	material	model	AM150C	AM250C	AM350C	AM450C	AM550C	AM650	AM850
	Element	Glass fiber,	Except option F	AM-EL150	AM-EL250	AM-EL350	AM-EL450	AM-EL550	AM-EL650	AM-EL850
4	assembly	others	For option F	AM-EL150-F	AM-EL250-F	AM-EL350-F	AM-EL450-F	AM-EL550-F	_	_

* Element assembly: With gasket (1 pc.) and O-ring (1 pc.)

* Refer to back page 6 for replacement of auto drain.

* Element assemblies for Made to Order (X6, X12, X15, X17, X20, X26, X37) are same as those for standard (see the above table).

Maximum Air Flow



Model Selection

for details.

AM850

Select a model in accordance with the following procedure taking the inlet pressure and the max. air flow rate into consideration. (Example) Inlet pressure: 0.6 MPa

Note) Sight glass is indicated in the figure for easy understanding of component parts. However, it differs from the actual

construction. Refer to dimensions on pages 23 through to 25

Max. air flow rate: 5 m³/min (ANR)

- 1. Obtain the intersecting point A of inlet pressure and max. air flow rate in the graph.
- 2. The AM650 is obtained when the max. flow line is above the intersecting point A in the graph.





Dimensions

AM150C to 550C







Combination of D: With auto drain (N.O.) and H: For medium air pressure



Option

J: Drain guide 1/4 female threaded



S, U: With differential pressure switch (with indicator)



T: With element service indicator



																											(mm)
Model	Port size	Α	в	с	D	Е	F	G					В	racł	ket re	elate	ed di	men	sions					Eler sen indicato dimer	nent vice r related nsions	Differ pres switch dimer	rential sure related nsions
									н	1	J	Κ	Т	U	L	М	V	Ν	0	Р	Q	R	S	w	X	Y	Z
AM150C	1/8, 1/4	158	10	99	63	20	63	10	173	56	20	5	6	6	12	6	10	35	54	70	26	4.5	1.6	24	37	32	41
AM250C	1/4, 3/8	172	14	113	76	20	76	10	190	66	24	8	6	6	12	6	10	40	66	80	28	5	2	27	37	36	41
AM350C	3/8, 1/2	204	18	145	90	20	90	10	222	80	28	8	7	7	14	7	12	50	80	95	34	5	2.3	32	37	42	41
AM450C	1/2, 3/4	225	20	166	106	20	106	10	246	90	31	10	9	9	18	9	15	55	88	111	50	9	3.2	37	37	43	41
AM550C	3/4, 1	259	24	200	122	20	122	15	278	100	33	10	9	9	18	9	15	65	102	126	60	10	3.2	39	37	51	41

Dimensions

AM650







Option





T: With element service indicator







Series AM

Dimensions

AM850







Option





Micro Mist Separator Series AMD

Can separate and remove aerosol state oil mist in compressed air and remove particles such as carbon or dust of more than 0.01 μ m. Use this product as a pre-filter for compressed air for precision instruments or clean room requiring higher clean air.

Modular connection is possible with AMD150C to 550C.

(For details, refer to page 61.)





AMD150C to 550C

AMD650/850





Made to Order (For details, refer to page 67.)

Model

Model	AMD150C	AMD250C	AMD350C	AMD450C	AMD550C	AMD650	AMD850		
Note) Rated flow (#min (ANR))	200	500	1000	2000	3700	6000	12000		
Port size	1/8, 1/4	1/4, 3/8	3⁄8, 1⁄2	1/2, 3/4	3⁄4, 1	1, 1 ¹ ⁄2	1 ¹ ⁄2, 2		
Mass (kg)	0.38	0.55	0.9	1.4	2.1	4.2	10.5		

Note) Max. flow at 0.7 MPa.

Max. flow varies depending on the operating pressure.

Refer to "Flow Characteristics" (page 29) and "Maximum Air Flow" (page 28).

Model/Free Standing Type

Model	AMD800	AMD900	AMD1000
Rated flow (#min (ANR))	8000	24000	40000
Port size	50(2B)JIS 10K FF flange	50(2B), 80(3B), 100(4B)JIS 10K FF flange	100(4B), 150(6B)JIS 10K FF flange
Mass (kg)	100	220	430

Model/Piping Support Type

Model	AMD801	AMD901
Rated flow (<i>t</i> /min (ANR))	8000	24000
Port size	50(2B)JIS 10K FF flange	50(2B), 80(3B), 100(4B)JIS 10K FF flange
Mass (kg)	50	140

Specifications

•	
Fluid	Compressed air
Max. operating pressure	1.0 MPa
Min. operating pressure*	0.05 MPa
Proof pressure	1.5 MPa
Ambient and fluid temperature	5 to 60°C
Nominal filtration rating	0.01 µm (Filtration efficiency: 99.9%)
Oil mist density at outlet	Max. 0.1 mg/m ³ (ANR)*
On mist density at outlet	(Before saturated with oil, less than 0.01 mg/m ³ (ANR) \approx 0.008 ppm)
Element life	2 years (1 year for flange type)
	or when pressure drop reached 0.1 MPa

* With auto drain: 0.1 MPa (N.O. type) or 0.15 MPa (N.C. type)

* Oil mist density at 30 mg/m³ (ANR) blown out by compressor.

Accessory

Applicable model	AMD150C	AMD250C	AMD350C	AMD450C	AMD550C	AMD650	AMD850
Bracket assembly (with 2 mounting screws)	AM-BM101	AM-BM102	AM-BM103	AM-BM104	AM-BM105	BM56	BM57

▲ Caution

- Be sure to read this before handling.
- Refer to back pages 1 and 2 for Safety Instructions, "Precautions for I
- Handling Pneumatic Devices" (M-03-E3A) for Common Precautions, I
- and back pages 3 through to 7 for Specific Product Precautions.



Series AMD

How to Order



Auto Drain Specifications/Option Combinations

 \bigcirc , \triangle : Plural options cannot be selected.

(i.e. Combinations such as C-FV, D-FHV, J-ST are not possible.)

(, , , , , , , , , , , , , , , , , ,							
Symbol	F	Н	R	S	U	Т	V
Auto drain specifications Nil	0	0	0	0	0	0	0
С			0	0	0	0	
D			0	0	0	0	\triangle
J	0	Ô	Ô	0	Ô	Ó	0

• Made to Order

("How to Order" and the applicable models are different from those shown on this page. Be sure to refer to "Made to Order".)

Symbol	Description	Page for details
Nil	—	—
X6	With differential pressure gauge (GD40-2-01)	P.68
X15	With IN-OUT flange	P.69
X17	With differential pressure gauge (GD40-2-01) and IN-OUT flange	P.69
X26	N.C., N.O. auto drain, drain piping type	P.70

• Option *3

Symbol	Description
Nil	—
F	Rubber material: Fluororubber
Н	For medium air pressure (1.6 MPa)
J	Drain guide 1/4 female thread *4
R	IN-OUT reversal direction
S	With differential pressure switch (125 VAC, 30 VDC) *5, Note)
U	With differential pressure switch (30 VDC) *5, Note)
Т	With element service indicator
V	Degreasing wash,*6 white vaseline

*4 Drain piping and piping for a stop valve such as ball valve are required.
 *5 Differential pressure gauge is included, (but not assembled).

*6 Only body/housing is degreasing washed.

Note) Order "U" if conformity to the EU directive is required.

Auto drain *3

Symbol	Description
Nil	Drain cock (Without auto drain)
С	N.C. auto drain
D	N.O. auto drain

*3 Refer to "Auto Drain Specifications/Option Combinations".

Options





SMC



Micro Mist Separator Series AMD



- Obtain the intersecting point A of inlet pressure and max, air flow rate in the graph.
 The AMD650 is obtained when the max, flow line is above the in-
- the AMD650 is obtained when the max, now line is above the intersecting point A in the graph.



Note) Make sure to select a model that has the max. flow line above the obtained intersecting point. With a model that has the max. flow line below the obtained intersecting point, the flow rate will be exceeded, thus leading to a problem such as being unable to satisfy the specifications.





Series AMD

Flow Characteristics/Select the model taking the max. flow capacity into consideration. (---- Element oil saturation ---- Initial condition)

Note) Compressed air over max. flow line in the table below may not meet the specifications of the product. It may cause damage to the element.

AMD150C











AMD90/901





AMD10□0



AMD80 //81 0.05 0.04 0.04 0.03 0.02 Max. flow line 0.2 4 6 8 10



Construction



Replacement Parts

1

2

No.	Description Motorial		Applicable	Model						
	Description	wateria	model	AMD150C	AMD250C	AMD350C	AMD450C	AMD550C	AMD650	AMD850
4	Element	Glass fiber,	Except option F	AMD-EL150	AMD-EL250	AMD-EL350	AMD-EL450	AMD-EL550	AMD-EL650	AMD-EL850
	assembly	others	For option F	AMD-EL150-F	AMD-EL250-F	AMD-EL350-F	AMD-EL450-F	AMD-EL550-F	_	

* Element assembly: With gasket (1 pc.) and O-ring (1 pc.)

* Refer to back page 6 for replacement of auto drain.

* Element assemblies for Made to Order (X6, X12, X15, X17, X20, X26, X37) are same as those for standard (see the above table).

AMD800/810/900/901/1000



Component Parts/Material

No	Description	Mod	Note	
INO.	Description	AMD800/810/90/1000	AMD801/811/9□1	Note
1	Filter case	SGP-E, SS400	SGP-E, SS400	
2	Cover	SS400	SGP-E, SS400	

Replacement Parts

No	Description	Matarial	Model						
INO.	Description	waterial	AMD800/810	AMD801/811	AMD900	AMD901	AMD1000		
3	Element	_	63174	63174	63174 3 pcs.	63174 3 pcs.	63174 5 pcs.		
4	Seal	NBR	63148	63148	63148 3 pcs.	63148 3 pcs.	63148 5 pcs.		
5	Seal	NBR	0.D112 x I.D90 x T3	_	O.D112 x I.D90 x T3 3 pcs.	_	O.D112 x I.D90 x T3 5 pcs.		
6	Gasket	V#6500	AL-61S	AL-60S	AL-63S	AL-62S	AL-31S		
7	O-ring	NBR	JIS B2401G35 1 pc.	JIS B2401G35 1 pc.	JIS B2401G35 3 pcs.	JIS B2401G35 3 pcs.	JIS B2401G35 5 pcs.		



Series AMD

Dimensions

AMD150C to 550C







Combination of D: With auto drain (N.O.) and H: For medium air pressure



Option

J: Drain guide 1/4 female threaded



S, U: With differential pressure switch (with indicator)



T: With element service indicator



																											(mm)
Model	Port size	A	в	с	D	Е	F	G	Bracket related dimensions													Element service indicator related dimensions		Differential pressure switch related dimensions			
									н	I	J	Κ	Т	U	L	М	V	Ν	0	Р	Q	R	S	w	X	Y	Z
AMD150C	1/8, 1/4	158	10	99	63	20	63	10	173	56	20	5	6	6	12	6	10	35	54	70	26	4.5	1.6	24	37	32	41
AMD250C	1/4, 3/8	172	14	113	76	20	76	10	190	66	24	8	6	6	12	6	10	40	66	80	28	5	2	27	37	36	41
AMD350C	3/8, 1/2	204	18	145	90	20	90	10	222	80	28	8	7	7	14	7	12	50	80	95	34	5	2.3	32	37	42	41
AMD450C	1/2, 3/4	225	20	166	106	20	106	10	246	90	31	10	9	9	18	9	15	55	88	111	50	9	3.2	37	37	43	41
AMD550C	3/4, 1	259	24	200	122	20	122	15	278	100	33	10	9	9	18	9	15	65	102	126	60	10	3.2	39	37	51	41

Dimensions

AMD150C to 550C, AMD650







Option





T: With element service indicator



Series AMD

Dimensions

AMD850





Option






Dimensions

AMD801/811/9□1



										(mm)
Model	Connection (Flange)	A	ø B	øC	D	E	F	G	Н	J
AMD801/811	50(2B)JIS 10K FF flange	400	280	150(6B)	760	150	270	1033	3	887
AMD9□1	50(2B), 80(3B), 100(4B)JIS 10K FF flange	620	445	300(12B)	795	300	520	1318	3	972

AMD800/810/90/1000



										(mm)
Model	Connection (Flange)	Α	ø B	øC	D	E	F	G	Н	Anchor bolt
AMD800/810	50(2B), 80(3B)JIS 10K FF flange	500	300	200(8B)	300	1300	1430	1520	20	M16 x <i>e</i> 400
AMD9D0	50(2B), 80(3B), 100(4B)JIS 10K FF flange	720	560	400	300	1320	1480	1585	24	M20 x <i>t</i> 500
AMD10□0	100(4B), 150(6B)JIS 10K FF flange	870	745	550	300	1380	1610	1740	24	M20 x <i>t</i> 500

Micro Mist Separator with Pre-filter Series AMH

500

1/4, 3/8

0.55

Max. flow varies depending on the operating pressure.

Can separate and remove aerosol state oil mist in compressed air and remove particles such as carbon or dust of more than 0.01 µm. Use this product as a pre-filter for compressed air for precision instruments or clean room requiring higher clean air.

The conventional pneumatic pressure line, AM series + AMD series have been integrated to achieve a reduction in installation space and in piping labor.

Modular connection is possible with AMH150C to 550C. (For details, refer to page 61.)





AMH150C to 550C

AMH650/850





1.0 MPa 0.05 MPa 1.5 MPa 5 to 60°C 0.01 µm (Filtration efficiency: 99.9%) Max. 0.1 mg/m3 (ANR)* (Before saturated with oil, less than 0.01 mg/m³ (ANR) ≈0.008 ppm) 2 years or when pressure drop reached 0.1 MPa * With auto drain: 0.1 MPa (N.O. type) or 0.15 MPa (N.C. type)

Compressed air

AMH150C AMH250C AMH350C AMH450C AMH550C AMH650

2000

1/2, 3/4

1.4

3700

3⁄4, 1

2.1

6000

1, 11/2

4.2

1000

3/8, 1/2

0.9

Refer to "Flow Characteristics" (page 39) and "Maximum Air Flow" below.

AMH850

12000

11/2, 2

10.5

AMH850

* Oil mist density at 30 mg/m3 (ANR) blown out by compressor.

Accessorv

Element life

Model

Port size

Mass (kg)

Fluid

Model

Rated flow (@min (ANR))

Specifications

Proof pressure

Max. operating pressure Min. operating pressure*

Nominal filtration density

Oil mist density at outlet

Ambient and fluid temperature

Note)

Note) Max. flow at 0.7 MPa.

200

1/8, 1/4

0.38

Applicable model	AMH150C	AMH250C	AMH350C	AMH450C	AMH550C	AMH650	AMH850
Bracket assembly (with 2 mounting screws)	AM-BM101	AM-BM102	AM-BM103	AM-BM104	AM-BM105	BM56	BM57

Model Selection

Select a model in accordance with the following procedure taking the inlet pressure and the max. air flow rate into consideration. (Example) Inlet pressure: 0.6 MPa Max. air flow rate: 5 m3/min (ANR)

1. Obtain the intersecting point A of inlet pressure and max. air flow rate in the graph.

The AMH650 is obtained when the max.

flow line is above the intersecting point A

10

Maximum Air Flow





Caution

in the graph.

Be sure to read this before handling. Refer to back pages 1 and 2 for Safety Instructions, "Precautions for I Handling Pneumatic Devices" (M-03-E3A) for Common Precautions, I and back pages 3 through to 7 for Specific Product Precautions.

SVC

36

Series AMH

How to Order



Auto Drain Specifications/Option Combinations

 \bigcirc, \triangle : Plural options cannot be selected.

(i.e. Combinations such as C-FV, D-FHV, J-ST are not possible.)

(••••		.,	0.01	0. 000.	
Symbol	F	Н	R	S	U	Т	V
Auto drain specifications Nil	O	0	0	0	0	0	0
С	\triangle		0	0	0	0	
D	\bigtriangleup	\bigtriangleup	0	0	0	0	
J	Ô	Ô	0	0	0	0	0

Made to Order

("How to Order" and the applicable models are different from those shown on this page. Be sure to refer to "Made to Order".)

Symbol	Description	Page for details
Nil	—	—
X6	With differential pressure gauge (GD40-2-01)	P.68
X15	With IN-OUT flange	P.69
X17	With differential pressure gauge (GD40-2-01) and IN-OUT flange	P.69
X26	N.C., N.O. auto drain, drain piping type	P.70

Option *3

Symbol	Description
Nil	_
F	Rubber material: Fluororubber
Н	For medium air pressure (1.6 MPa)
J	Drain guide 1/4 female threaded *4
R	IN-OUT reversal direction
S	With differential pressure switch (125 VAC, 30 VDC) *5, Note)
U	With differential pressure switch (30 VDC) *5, Note)
Т	With element service indicator
V	Degreasing wash,*6 white vaseline

*4 Drain piping and piping for a stop valve such as ball valve are required.

*5 Differential pressure switch is included, (but not assembled).

*6 Only body/housing is degreasing washed.

Note) Order "U" if conformity to the EU directive is required.

Auto drain *3

Symbol	Description
Nil	Drain cock (Without auto drain)
С	N.C. auto drain
D	N.O. auto drain

*3 Refer to "Auto Drain Specifications/Option" Combinations".

Options





SMC

Can be pipied to the drain exhaust port. 1/4 female threaded Symbol U: With differential pressure switch (with indicator) Saturation of the separator can be observed visually or by an electrical signal. (Element life check) The rated contact voltage is different from "S" Max. contact capacity: 10 W DC Rated contact voltage (max. operating current): 30 V DC (0.33 A)



Micro Mist Separator with Pre-filter Series AMH



Note) Refer to "How to Order Bowl Assembly" on page 63.

: Available

: Not available

Auto Drain Specifications/Option Combinations

-	-							
Auto droip	ana aifiantiana (Ontian	Auto drain specifications		Option		Applicable model		
Auto drain :	specifications/Option		D	J	R	Т	AMH650	AMH850
Auto drain specifications	N.O. auto drain	D			0	0	0	0
	Drain guide 1/4	J			0	0	0	
Option	IN-OUT reversal direction	R	0	0		0	0	0
	With element service indicator	Т	0	0	0		0	0

Series AMH

Flow Characteristics/Select the model taking the max. flow capacity into consideration. (----- Element oil satura

(----- Element oil saturation ---- Initial condition)

Note) Compressed air over max. flow line in the table below may not meet the specifications of the product. It may cause damage to the element.

AMH150C





AMH850



AMH250C











AMH650



Micro Mist Separator with Pre-filter Series AMH

Construction



* Element assembly: With gasket (1 pc.) and O-ring (1 pc.)

For option F AMH-EL150-F

* Refer to back page 6 for replacement of auto drain.

others

* Element assemblies for Made to Order (X6, X12, X15, X17, X20, X26, X37) are same as those for standard (see the above table).

Series AMH

Dimensions

AMH150C to 550C







Combination of D: With auto drain (N.O.) and H: For medium air pressure



Option

J: Drain guide 1/4 female threaded



S, U: With differential pressure switch (with indicator)



T: With element service indicator



																											, mini)
Model	Port size	A	в	с	D	Е	F	G		Bracket related dimensions									Eler serv indicato dimer	nent vice r related nsions	Differ pres switch dimer	ential sure related nsions					
									н	1	J	Κ	Т	U	L	М	V	Ν	0	Ρ	Q	R	S	w	X	Υ	Ζ
AMH150C	1/8, 1/4	158	10	99	63	20	63	10	173	56	20	5	6	6	12	6	10	35	54	70	26	4.5	1.6	24	37	32	41
AMH250C	1/4, 3/8	172	14	113	76	20	76	10	190	66	24	8	6	6	12	6	10	40	66	80	28	5	2	27	37	36	41
AMH350C	3/8, 1/2	204	18	145	90	20	90	10	222	80	28	8	7	7	14	7	12	50	80	95	34	5	2.3	32	37	42	41
AMH450C	1/2, 3/4	225	20	166	106	20	106	10	246	90	31	10	9	9	18	9	15	55	88	111	50	9	3.2	37	37	43	41
AMH550C	3/4, 1	259	24	200	122	20	122	15	278	100	33	10	9	9	18	9	15	65	102	126	60	10	3.2	39	37	51	41

SMC

Dimensions

AMH650







Option





T: With element service indicator



Series AMH

Dimensions

AMH850





Option

T: With element service indicator





Super Mist Separator Series AME

Can separate and adsorb aerosol state fine oil particles in compressed air and change the oil lubricating compressed air to oilless air or equivalent.

Use this product for filtration of compressed air requiring higher clean air for painting lines, compressed air for clean rooms and/or equipment where oils must be avoided.

Indicates the filter element life by a color change. Accordingly, the replacement time can be judged visually. (A red color spot indicates the replacement time.)

A Caution

By all means the "AM" series should be used as a pre-filter.

Modular connection is possible with AME150C to 550C.

(For details, refer to page 61.)



AME150C to 350C AME450C/550C



Symbol

AME650/850



Made to Order (For details, refer to page 67.)

Model

mouci							
Model	AME150C	AME250C	AME350C	AME450C	AME550C	AME650	AME850
Note) Rated flow (ℓ/min (ANR))	200	500	1000	2000	3700	6000	12000
Port size	1/8, 1/4	1/4, 3/8	3⁄8, 1⁄2	1/2, 3/4	3⁄4, 1	1, 1 ½	1 ¹ ⁄2, 2
Mass (kg)	0.3	0.48	0.8	1.3	2.0	4.2	10.5

Note) Max. flow at 0.7 MPa.

Max. flow varies depending on the operating pressure.

Refer to "Flow Characteristics" (page 47) and "Maximum Air Flow" (page 47).

Specifications

•	
Fluid	Compressed air
Max. operating pressure	1.0 MPa
Min. operating pressure	0.05 MPa
Proof pressure	1.5 MPa
Ambient and fluid temperature	5 to 60°C
Nominal filtration rating	0.01 μm (Filtration efficiency: 99.9%)
Cleanliness at outlet	Less than 100 particles of 0.3 μm or larger per cubic foot
	[Less than 35 particles per 10 liters (ANR)]
Oil mist donsity at outlet	Max. 0.01 mg/m ³ (ANR)
On mist density at outlet	(≈0.008 ppm)
Flowent life	Element color indicator (Replace the element when a red color
Element life	spot occurred on the surface.)

Accessory

Applicable model	AME150C	AME250C	AME350C	AME450C	AME550C	AME650	AME850
Bracket assembly (with 2 mounting screws)	AM-BM101	AM-BM102	AM-BM103	AM-BM104	AM-BM105	BM56	BM57

A Caution

Be sure to read this before handling.	
Refer to back pages 1 and 2 for Safety	Instructions, "Precautions for I
Handling Pneumatic Devices" (M-03-E	3A) for Common Precautions, I
and back pages 3 through to 7 for Speci	fic Product Precautions.

Series AME



Options

Symbol F: Rubber material: Fluororubber

Fluororubber is used for the parts such as O-ring and gasket.

Symbol V: Degreasing wash, white vaseline

Body/housing is degreasing washed. The lubrication grease for O-ring and gasket is changed to white vaseline.

Symbol H: For medium air pressure (1.6 MPa)

10

1

Can be used up to 1.6 MPa at maximum.

Symbol R: IN-OUT reversal direction

Air flow in the separator is changed to right to left. (Air flow direction of the standard: Left to right.)

Super Mist Separator Series AME

Note) Refer to "How to Order Bowl Assembly" on page 63.



Series AME

Flow Characteristics (Element initial condition)

Note) Compressed air over max. flow line in the table below may not meet the specifications of the product. It may cause damage to the element.

AME450C

AME550C

0.05

0.04

0.03

0.02

0.01

0

0

Pressure drop (MPa)





0.05 0.04 Pressure drop (MPa) Max, flow line 0.03 0.02 0.01 0 0 1000 2000 3000 Air flow rate (*ℓ*/min (ANR))

0

2000

0.1

4000

Air flow rate (*ℓ*/min (ANR))

Max. flow line







AME350C



Model Selection

Select a model in accordance with the following procedure taking the inlet pressure and the max. air flow rate into consideration. (Example) Inlet pressure: 0.6 MPa

- Max. air flow rate: 5 m3/min (ANR)
- 1. Obtain the interecting point A of inlet pressure and max. air flow rate in the graph.
- 2. The AME650 is obtained when the max. flow line is above the intersecting point A in the graph.

Note) Make sure to select a model that has the max. flow line above the obtained intersecting point. With a model that has the max. flow line below the obtained intersecting point, the flow rate will be exceeded, thus leading to a problem such as being unable to satisfy the specifications.

Maximum Air Flow

6000



47

Construction



Replacement Parts

No	Description	Motorial	Applicable				Model			
INO.	Description	material	model	AME150C	AME250C	AME350C	AME450C	AME550C	AME650	AME850
	Element	Glass fiber,	Except option F	AME-EL150	AME-EL250	AME-EL350	AME-EL450	AME-EL550	AME-EL650	AME-EL850
4	assembly	others	For option F	AME-EL150-F	AME-EL250-F	AME-EL350-F	AME-EL450-F	AME-EL550-F	—	

* Element assembly: With gasket (1 pc.) and O-ring (1 pc.)

* Element assemblies for Made to Order (X12, X20) are same as those for standard (see the above table).

Series AME

Dimensions

AME150C to 350C





																							(mm)
Model Port size A B C D E F G Bracket related d								ed di	mens	sions													
Model	Port size	A	P		U			G	I	Ν	J	κ	U	V	L	Μ	W	0	Ρ	Q	R	S	Т
AME150C	1/8, 1/4	83	10	54	63	7.5	63	10	98.5	56	20	5	6	6	12	6	10	35	70	26	54	4.5	1.6
AME250C	1/4, 3/8	103	14	73	76	5	76	10	121	66	24	8	6	6	12	6	10	40	80	28	66	5	2
AME350C	3/8. 1/2	132	18	98	90	5	90	10	150	80	28	8	7	7	14	7	12	50	95	34	80	5	2.3

Dimensions

AME450C/550C



																							(mm)
Madal	Dort oizo	•	Р	^		E	E	~	ы					Bra	cket ı	relate	d din	nensi	ons				
Model	Port size	A	P			E		G		I	Ν	J	κ	U	V	L	М	W	0	Р	Q	R	Т
AME450C	1/2, 3/4	151	20	105	106	3	106	10	36	172	90	31	10	9	9	18	9	15	55	111	50	88	3.2
AME550C	3/4, 1	187	24	130	122	3	122	15	44	206	100	33	10	9	9	18	9	15	65	126	60	102	3.2

Series AME

Dimensions

AME650/850







																				(mm)
Madal	Dort oizo	•	Р	6	D	E	E	<u> </u>	ы				Bra	cket re	lated d	imensi	ons			
woder	Port size	A	Р				F	FGF		I	J	K	L	М	N	0	Ρ	Q	R	S
AME650	1, 11/2	291	32	167	160	—	160	10	66	314	40	15	20	11	150	85	180	76	136	4.5
AME850	11/2, 2	403	42	235	220		220	10	96	406	30	15	24	13	180	120	220	110	184	6

Odor Removal Filter Series AMF

Efficiently can remove odor in compressed air with an activated carbon element. The unit is designed for use in the area such as a clean room where odors must be avoided.

Can remove odor and gas ingredients in compressed air. Activated carbon element with large filtration area.

Easy replacement of elements.

Modular connection is possible with AMF150C to 550C.

(For details, refer to page 61.)



AMF150C to 350C AMF450C/550C



AMF650/850





Made to Order (For details, refer to page 67.)

Model

measi							
Model	AMF150C	AMF250C	AMF350C	AMF450C	AMF550C	AMF650	AMF850
Note) Rated flow (#min (ANR))	200	500	1000	2000	3700	6000	12000
Port size	1/8, 1/4	1/4, 3/8	3⁄8, 1⁄2	1/2, 3/4	3⁄4, 1	1, 1 ¹ ⁄2	1 ¹ ⁄2, 2
Mass (kg)	0.3	0.48	0.8	1.3	2.0	4.2	10.5

Note) Max. flow at 0.7 MPa.

Max. flow varies depending on the operating pressure.

Refer to "Flow Characteristics" (page 55) and "Maximum Air Flow" (page 54).

Model/Free Standing Type

Model	AMF800	AMF900	AMF1000
Rated flow (<i>t</i> /min (ANR))	8000	24000	40000
Port size	50(2B)JIS 10K FF flange	50(2B), 80(3B),100(4B)JIS 10K FF flange	100(4B),150(6B)JIS 10K FF flange
Mass (kg)	90	200	410

Model/Piping Support Type

Model	AMF801	AMF901
Rated flow (<i>t</i> /min (ANR))	8000	24000
Port size	50(2B)JIS 10K FF flange	50(2B), 80(3B),100(4B)JIS 10K FF flange
Mass (kg)	40	120

Specifications

•	
Fluid	Compressed air
Max. operating pressure	1.0 MPa
Min. operating pressure	0.05 MPa
Proof pressure	1.5 MPa
Ambient and fluid temperature	5 to 60°C
Nominal filtration rating	0.01 μm (Filtration efficiency: 99.9%)
Cleanliness at outlet	Less than 100 particles of 0.3 μm or larger per cubic foot [Less than 35 particles per 10 liters (ANR)] (The "AME" series is required on the inlet side.)
Oil mist density at outlet	Max. 0.004 mg/m³ (ANR) (≈0.0032 ppm) (The "AME" series is required on the inlet side.)

Accessory (Option)

Applicable model	AMF150C	AMF250C	AMF350C	AMF450C	AMF550C	AMF650	AMF850
Bracket assembly (with 2 mounting screws)	AM-BM101	AM-BM102	AM-BM103	AM-BM104	AM-BM105	BM56	BM57

▲ Caution

L

Be sure to read this before handling.

Refer to back pages 1 and 2 for Safety Instructions, "Precautions for I Handling Pneumatic Devices" (M-03-E3A) for Common Precautions, and back pages 3 through to 7 for Specific Product Precautions.

Series AMF



Options

Symbol F: Rubber material: Fluororubber

Fluororubber is used for the parts such as O-ring and gasket.

Symbol V: Degreasing wash, white vaseline

Body/housing is degreasing washed. The lubrication grease for O-ring and gasket is changed to white vaseline.

Symbol H: For medium air pressure (1.6 MPa)

10

1

Can be used up to 1.6 MPa at maximum.

Symbol R: IN-OUT reversal direction

Air flow in the separator is changed to right to left. (Air flow direction of the standard: Left to right.)

Odor Removal Filter Series AMF



Model Selection

Select a model in accordance with the following procedure taking the inlet pressure and the max. air flow rate into consideration. (Example) Inlet pressure: 0.6 MPa

- Max. air flow rate: 5 m3/min (ANR)
- 1. Obtain the intersecting point A of inlet pressure and max. air flow rate in the graph.
- The AMF650 is obtained when the max. flow line is above the intersecting point A in the graph.



Note) Make sure to select a model that has the max. flow line above the obtained intersecting point. With a model that has the max. flow line below the obtained intersecting point, the flow rate will be exceeded, thus leading to a problem such as being unable to satisfy the specifications.

Maximum Air Flow





Series AMF

Flow Characteristics/Refer to "Model Selection" on page 54. (Element initial condition)

Note) Compressed air over max. flow line in the table below may not meet the specifications of the product. It may cause damage to the element.

AMF550C

AMF650

0.03

0.02

0.015

0.01

0.005

°ò

Pressure drop (MPa)

AMF150C 0.02 Lessure drop (MPa) 0.00 0.00 0.00 0.00 Max. flow line 50 100 150 200 250





AMF900/901 0.007 ND 0.006 Pressure drop (MPa) (MPa

6

12

20

30

40

18

24



0.001

C









AMF800/801

1500

55



Odor Removal Filter Series AMF

Construction



4 assembly diass moet, Exceptional Anni-Letion Anni-Le

* Element assembly: With gasket (1 pc.) and O-ring (1 pc.)

* Element assemblies for Made to Order (X12, X20) are same as those for standard (see the above table).

AMF80□/90□/1000



Component Parts/Material

AMF-EL450-F

No	Description	Mod	lel	Note
INO.	Description	AMF800/900/1000	AMF801/901	note
1	Filter case	SGP-E: SS400	SGP-E: SS400	
2	Cover	SS400	SGP-E: SS400	

AMF-EL550-F

Replacement Parts

No	Description	Matarial		Model										
INO.	Description	waterial	AMF800	AMF801	AMF900	AMF901	AMF1000							
3	Element	_	63271	63271	63271 3 pcs.	63271 3 pcs.	63271 5 pcs.							
4	Seal	NBR	63148	63148	63148 3 pcs.	63148 3 pcs.	63148 5 pcs.							
5	Seal	NBR	O.D112 x I.D90 x T3 1 pc.	—	O.D112 x I.D90 x T3 3 pcs.	_	O.D112 x I.D90 x T3 5 pcs.							
6	Gasket	V#6500	AL-61S	AL-60S	AL-63S 3 pcs.	AL-62S	AL-31S							
7	O-ring	NBR	JIS B2401G35 1 pc.	JIS B2401G35 1 pc.	JIS B2401G35 3 pcs.	JIS B2401G35 3 pcs.	JIS B2401G35 5 pcs.							

Series AMF

Dimensions

AMF150C to 350C





																							(mm)
Madal	Dort oizo		Б	C	2	E	E	^					Br	acke	t relat	ed di	imens	sions					
Model	Port size	A	P		U			G	I	N	J	κ	U	V	L	Μ	W	0	Ρ	Q	R	S	Т
AMF150C	1/8, 1/4	83	10	54	63	7.5	63	10	98.5	56	20	5	6	6	12	6	10	35	70	26	54	4.5	1.6
AMF250C	1/4, 3/8	103	14	73	76	5	76	10	121	66	24	8	6	6	12	6	10	40	80	28	66	5	2
AMF350C	3/8, 1/2	132	18	98	90	5	90	10	150	80	28	8	7	7	14	7	12	50	95	34	80	5	2.3

SMC

Dimensions

AMF450C/550C



																							(mm)
Madal	Dort oizo	•	Р	^	D	E	E	^	ы					Bra	cket ı	relate	d din	nensi	ons				
Model	Port size	A	P			E		G	п	I	Ν	J	κ	U	V	L	М	W	0	Р	Q	R	Т
AMF450C	1/2, 3/4	151	20	105	106	3	106	10	36	172	90	31	10	9	9	18	9	15	55	111	50	88	3.2
AMF550C	3/4, 1	187	24	130	122	3	122	15	44	206	100	33	10	9	9	18	9	15	65	126	60	102	3.2

Series AMF

Dimensions

AMF650/850







F

(mm)

																				()
Model	Port cizo	•	Б	^	n	E	E	F G H Bracket related dimensions	ons											
woder	FUILSIZE	~	В				F	G	п	I	J	K	L	M	N	0	Р	Q	R	S
AMF650	1, 11/ ₂	291	32	167	160		160	10	66	314	40	15	20	11	150	85	180	76	136	4.5
AMF850	11/2, 2	403	42	235	220		220	10	96	406	30	15	24	13	180	120	220	110	184	6

Dimensions

AMF801/901



										(mm)
Model	Connection (Flange)	Α	ø B	øC	D	E	F	G	Н	J
AMF801	50(2B)JIS 10K FF flange	400	280	150(6B)	550	150	270	823	3	797
AMF901	50(2B), 80(3B), 100(4B)JIS 10K FF flange	620	445	300(12B)	570	300	520	1093	3	867

AMF800/900/1000



										(mm)
Model	Connection (Flange)	Α	øB	øC	D	E	F	G	Н	Anchor bolt
AMF800	50(2B)JIS 10K FF flange	500	330	200(8B)	300	1070	1200	1290	20	M16 x <i>e</i> 400
AMF900	50(2B), 80(3B), 100(4B)JIS 10K FF flange	720	560	400	300	1070	1230	1335	24	M20 x <i>e</i> 500
AMF1000	100(4B), 150(6B)JIS 10K FF flange	870	745	550	300	1090	1320	1450	24	M20 x <i>¢</i> 500

Series AMF

Spacer for Modular Connection

Select a spacer from those listed below when combining modular type AFF2C to 22C, AM 150C to 550C. The spacer must be ordered separately. (Note: Spacer with bracket (Y200T to Y600T) cannot be used.)





Combination examples of modular applicable products



Spacer



Replacement Parts

Description	Motorial			Part no.		
Description	Material	Y200	Y300	Y400	Y500	Y600
Seal	HNBR	Y200P-061S	Y300P-060S	Y400P-060S	Y500P-060S	Y600P-060S

SMC

Piping Adapter



Dimension	s					(mm)
	Thread type	e and port size				
Part no.	Male thread side A	Female thread side B	С	D	Е	Material
IDF-AP609	R 3/8	NPT 3/8	30	15	22	Brass

Bowl Assembly AFF-CA /AM -CA

Bowl Assembly

AM-CA450C

AM-CA550C

Bowl assembly for the AFF and AMD series can be replaced without removing the main body from piping if the drain exhaust specification is to be changed from the drain cock type to the auto drain type or if the bowl has been damaged.



Auto Drain Specifications/ Option Combinations

 \bigcirc : Available \square : Not available \triangle : Plural options cannot be selected.

(i.e. Combinations such as C-FV, D-FHV are not possible.)

Symbol	F	Н	V
Α	0	0	0
С			\bigtriangleup
D		\bigtriangleup	\bigtriangleup
J	0	0	0



AFF11C, AM450C, AMD450C, AMH450C, AMG450C

AFF22C, AM550C, AMD550C, AMH550C, AMG550C

Bowl Assembly AFF-CA

How to Order Bowl Assembly

SMC



650 850

AFF-CA /AM -CA

Dimensions: AFF, AM, AMD, AMH, AMG Series

Size: AFF2C to 22C, AFF37B, AM $\square150C$ to 550C, AM $\square650$



				(mm)
AFF series	AM, AMD, AMG, AMH series	•	Р	<u> </u>
Size	Size	A	Р	C
2C	150C	134	63	148
4C	250C	139	76	153
8C	350C	162	90	176
11C	450C	178	106	192
22C	550C	202	122	216
37B	650	245	160	259

Note 1) Model no. labels are not affixed to the AM-CA150C to 550C. Note 2) Select according to the body thread type. Applicable tubing size for one-touch fitting Rc, G: Ø10 NPT: Ø3/8 inch

Size: AFF75B, AM B50





SMC

Bowl Assembly **AFF-CA /AM -CA**

Dimensions: AME, AMF Series

■ AME150C to 550C, AMF150C to 550C



		(mm)
AME, AMF series	•	в
Size	~	Б
150	60	63
250	70	76
350	90	90
450	104	106
550	130	122

AME650/850, AMF650/850



		(mm)
AME, AMF series	•	Р
Size	~	В
650	225	160
850	319	120

Compressed Air Cleaning Filter Series Made to Order/Special Specifications Please consult with SMC for detailed specifications, size and delivery.

Made to Order

Contonto	Sumbol			Арр	licable m	odel			Reference
Contents	Symbol	AFF	АМ	AMD	AME	AMF	AMG	АМН	page
1. With Differential Pressure Gauge (GD40-2-01)	X6	•	•	•	_	_	_	•	DCO
2. With Differential Pressure Switch (With Indicator)	X37	•	•	•			_	•	P.00
3. With IN-OUT Flange	X15	•	•	•	_	_	•	•	DEO
4. With Pressure Differential Gauge (GD40-2-01), IN-OUT Flange	X17	•	•	•	_			•	P.09
5. N.C., N.O. Auto Drain, Drain Piping Type	X26	•	•	•		_	•	•	P 70
6. White Vaseline Specifications	X12	•	•	•	igodot	•	•	•	1.70
7. Mist Separator for High Flow Rate (0.3 $\mu\text{m})$	X13			_	_		_	_	P.71

Special Specifications

Contents		Applicable model						Reference
		АМ	AMD	AME	AMF	AMG	АМН	page
Clean Series (10-Series)		•	•	•	•	—	•	0.72
Copper-free, Fluorine-free (20-Series)		•				•		F./2

Compressed Air Cleaning Filter Series Made to Order 1



Please consult with SMC for detailed specifications, size and delivery.

1. With Differential Pressure Gauge (GD40-2-01)

A differential pressure gauge that keeps track of the filter life is installed on the filter itself. This facilitates piping and achieves a compact design.



2. With Differential Pressure Switch (With indicator) (125 VAC, 30 VDC)

Allows visual confirmation of differential pressure which indicates the element life. The built-in contact enables remote control.

Specifications



ingres

The AMG series is not applicable since water drops could ingress inside its differential pressure gauge, resulting in malfunction or damage to the product.

Dimensions



			(mm)
AFF series	AM, AMD, AMH series	Dort oizo	^
Size	Size	Port size	A
37B	650	1, 1 ½	352
75B	850	11/2,2	501

Dimensions



				(mm)
AFF series	AM, AMD, AMH series	Dort oizo	•	Р
Size	Size	Port size	A .	Б
2C	150C	1/8, 1/4	239	80
4C	250C	1/4, 3/8	252	80
8C	350C	3/8, 1/2	284	80
11C	450C	1/2, 3/4	305	80
22C	550C	3/4, 1	339	80
37B	650	1, 1 ¹ /2	391	80
75B	850	1 ¹ ⁄2, 2	541	80

Compressed Air Cleaning Filter Series Made to Order 2



Please consult with SMC for detailed specifications, size and delivery.

3. With IN-OUT Flange

Makes flange piping easier when filter ports on IN and OUT are flange connection. (Flange material: Carbon steel)



Accessory*

Port size*

4. With Differential Pressure Gauge (GD40-2-01), IN-OUT Flange

The differential pressure gauge is mounted on the main body to monitor the life of a filter by checking its clogging status. Ports on IN and OUT are flange connection type. (Flange material: Carbon steel)



Dimensions

Thread type*

AMH

Body size³



				(11111)
AFF series Size	AM, AMD, AMG, AMH series Size	Connection	Α	в
11C	450C	15(1/2B), 20(3/4B), 25(1B) JIS 10K FF flange	240	255
22C	550C	20(3/4B), 25(1B) JIS 10K FF flange	260	297
37B	650	25(1B), 40(1 ½B) JIS 10K FF flange	300	349
75B	850	40(1 ½B), 50(2B) JIS 10K FF flange	380	497

Dimensions

. .

SMC



malfunction or damage to the product.

					(11111)
AFF series	AM, AMD, AMH series	Connection	۸	Р	<u> </u>
Size	Size	Connection	A	Р	C
11C	450C	15(1/2B), 20(3/4B), 25(1B) JIS 10K FF flange	305		240
22C	550C	20(3/4B), 25(1B) JIS 10K FF flange	339		260
37B	650	25(1B), 40(1 ½B) JIS 10K FF flange	391	80	300
75B	850	40(1 ½B), 50(2B) JIS 10K FF flange	541		380

Compressed Air Cleaning Filter Series Made to Order 3



Please consult with SMC for detailed specifications, size and delivery.

6. White Vaseline Specifications

Changed the grease for O-rings and gaskets as lubricant to white

5. N.C., N.O. Auto Drain, Drain Piping Type

Drain piping type (drain guide specification) to the drain exhaust from N.C. auto drain and N.O. auto drain. N.C. type is not available for the AFF37B and $AM\square650$.



vaseline.

Dimensions



			(11111)
AFF series	AM, AMD, AMG, AMH series	Dort oizo	•
Size	Size	Port size	A
2C	150C	1/8, 1/4	159
4C	250C	1/4, 3/8	172
8C	350C	3/8, 1/2	204
11C	450C	1/2, 3/4	225
22C	550C	3/4, 1	259
37B	650	1, 1 ¹ ⁄2	311
Compressed Air Cleaning Filter Series Made to Order 4



Please consult with SMC for detailed specifications, size and delivery.

7. Mist Separator for High Flow Rate (0.3 µm)

Use this product when the conventional mist separator (AM series) cannot dispose of a high flow rate. The specifications other than the nominal filtration rating are all equivalent to that of the AFF75A to 220A.



Compressed Air Cleaning Filter Series Special Specifications

Please consult with SMC for detailed specifications, size and delivery.

Clean Series (10-Series)

Clean Series products are used in cleaner environments such as in clean rooms as compared to a general factory environment. For further details, refer to the Clean Series catalog.

Copper-free, Fluorine-free (20-Series)

To eliminate effects on color CRTs, etc. by copper ion or fluorine resin, copper materials are electroless-nickel plated or changed to copper-free materials to prevent the generation of copper ions. (It is not applicable to the AMD, AME, AMF and AMH series because those include fluorine resin in the filter material of the element.)

Specifications



Note) "20-" is only applicable with N.C. auto drain (C) or N.O. auto drain (D). Drain cock and drain guide are copper-free, fluorine-free as standard.

Specifications



Note) "20-" is only applicable with N.C. auto drain (C) or N.O. auto drain (D). Drain cock and drain guide are copper-free, fluorine-free as standard



Specifications

AMF

Thread type*

Accessory

Description

Bracket

Port size*

Nil

F

н

R

Body size*

Symbol

Nil

в



Option Note)

Rubber material: Fluororubber

IN-OUT reversal direction

Note) F and H are only applicable to the

AME, AMF150C to 550C.

For medium air pressure (1.6 MPa)

Related Products: Auto Drain Valve Series AD402/600

Drain is automatically discharged in a reliable manner, without requiring human operators.

Highly resistant to dust and corrosion, operates reliably, and a bowl guard is provided as standard equipment.





AD402

AD600



Model/Specifications

Model	AD402	AD600
Proof pressure	1.5 MPa	1.5 MPa
Max. operating pressure	1.0 MPa	1.0 MPa
Operating pressure range Note)	0.1 to 1.0 MPa	0.3 to 1.0 MPa
Ambient and fluid temperature	-5 to 60°C (No freezing)	–5 to 60°C (No freezing)
Port size	1/4, 3/8, 1/2	3⁄4, 1
Drain port size	3/8	3⁄4, 1
Mass (g)	620	2100

Note) 400 *t*/min (ANR) or more

Specific Product Precautions

- Be sure to read this before handling.

Refer to back pages 1 and 2 for Safety Instructions, "Precautions for Handling Pneumatic Devices" (M-03-E3A) for Common Precautions.

Selection

∧ Warning

I.

Use the auto drain under the following operating conditions in order to prevent malfunction

- 1) Operate the compressor above 3.7 kw {400 e/min (ANR)}.
- Use the AD402 at an operating pressure above 0.1 MPa and AD600 above 0.3 MPa.

Piping

MWarning

Piping should be done under the following conditions in order to prevent malfunction. For drain piping, use a pipe whose I.D. is not less than ø10 and length not more than 5 m. Avoid riser piping.



Construction/Dimensions



1/4 . 3/8 . 1/2 \$82 14 Valve assembly (1) Body 2 O-ring 3 Gauze (7) Lever Valve (9) 184 Chamber 6 Float (5) 1) Spring Bowl 10 8 Piston Long hole 12 of chamber ④ O-ring Drain guide 13 Drain 3/8



No. Description

INO.	Description	Material
1	Body	Aluminum die-casted

Working Principle (AD402)

• When no pressure is applied inside the bowl (10, float (5) descends of its own weight and valve (9) closes the chamber (6) hole. Piston (8) is pushed down by spring (1), and drain passes through the chamber's long hole (12) to enter the housing and is discharged.

When pressure is applied inside the bowl:
When pressure is 0.1 MPa or more, it overcomes the force of spring 1, allowing the piston 8 to ascend, and comes in contact with O-ring 4. Thus, the inside of the bowl 10 is isolated from the outside.

• When drain has accumulated:

Float (5) ascends due to flotation and opens the chamber hole (6), allowing the pressure to enter the chamber (6). Piston (8) descends due to internal pressure and the force of spring (1), and the accumulated drain is discharged through drain guide (3).

Replacement Parts

No	Description	Motorial	Model	
INO.	Description	Material	AD402	AD600
2	O-ring	NBR	113136	JIS B2401G-100
3	Gauze	Stainless steel	20062	—
Note 1)	Internal assembly	—	AD34PA	_
8	Piston assembly	_		20025A

Note 1) Internal assembly: Assembly for parts ④ to ⑫ except ⑩.

Note 2) Part no. for bowl assembly: AD34

Note 3) Part no. for bowl 10: 201016

Related Products: Motor Operated Auto Drain Series ADN200

Reliably discharges even highly viscous drain

 Highly resistant to dust and highly viscous drain, the valve opens and closes reliably to discharge the drain.

High drain discharge capacity

- With a large discharge port, a large amount of drain can be discharged in a single operation.
- Elimination of residual drain inside the tank and pipes prevents the generation of foreign matter such as dried rust or drain, which could adversely affect the equipment located on the outlet side.

Low power consumption: 4 W

- A long pipe can also be connected to the discharge port.
- Can be connected directly to a compressor.



Model/Specifications

Model	ADM200-□□-□
Fluid	Air
Max. operating pressure	1.0 MPa
Proof pressure	1.5 MPa
Ambient and fluid temperature	–5 to 60°C (No freezing)
Operating cycle [*]	1 time in a minute (Standard)
Operating time	2 sec./time (Standard)
Power source	100, 200 VAC 51/60 Hz, Other
Power consumption	4 W
Bort oizo	IN: 3/8, 1/2
FUILSIZE	OUT: 3⁄8
Mass	550 g

* If the operating cycle is twice in a minute (operating time 2 sec. x 2) operating time is 4 sec. each minute.

▲ Specific Product Precautions

- Be sure to read before handling.
- Be sure to read before handling.
- Refer to back pages 1 and 2 for Safety Instructions, "Precautions for Handling Pneumatic Devices" (M-03-E3A) for Common Precautions.

Mounting

▲ Warning

- Install this product after discharging the drainage that has already accumulated in the tank. Otherwise, it could lead to malfunction.
- 2. Install this product, so that the drain port could face downwards. Otherwise, it could lead to malfunction.

Provide a stop valve before the ADM200 to facilitate maintenance and inspection.

∕∂SMC

∕∆Warning

Piping should be done under the following conditions in order to prevent malfunction. For drain piping, use a pipe whose I.D. is not less than ø5 and length not more than 5 m. Avoid riser piping.

Piping



▲Caution

If the valve becomes clogged with debris, press the manual button to flush out the debris. Otherwise, it could lead to malfunction.

How to Order								
ADM200-031-0								
	Thread	d type				• Opera	ating ti	me/Applicable compressor
	Nil	RC	-			Nil	2 sec/m	nin (1 time/min) /3.7 to 37 kW
			-			4	4 sec/m	nin (2 times/min) /37 to 75 kW
	Г	G	J			6	6 sec/m	nin (3 times/min) /75 to 110 kW
						8	8 sec/m	nin (4 times/min) /220 to 370 kW
_		Poi	t size					
[Symbol	IN	OUT	4	Vo	ltage		
	03	3⁄8	3⁄8		1	100 VAC	⁵⁰ / ₆₀ Hz	
	04	1/2	3⁄8		2	200 VAC	⁵⁰ / ₆₀ Hz	
					3	240 VAC	⁵⁰ / ₆₀ Hz	
					4	110 VAC	⁵⁰ / ₆₀ Hz	
					5	220 VAC	⁵⁰ / ₆₀ Hz	
					6	24 V	DC	
				L	7	12 V	DC	

Mounting Example



Construction/Dimensions



Component Parts

No.	Description	Material	Note
1	Body	Aluminum die-casted	Chrome treated
2	Сар	Aluminum die-casted	Chrome treated

Replacement Parts

No.	Description	Material	Part no.
3 Note)	Motor	_	812PG-voltage
4	Cam	Cast steel	Operating time 201324 (Nil) 201325 (4) 201326 (6) 201327 (8)
5	Valve assembly	Brass, NBR	20137-1A
6	O-ring	NBR	S-16

Note) Motor part no. in the case of 100 VAC: 812PG-AC100V

Related Products: Heavy Duty Auto Drain Series ADH4000

Easy maintenance

Can maintain without removing the existing piping.

No need for electric power and no waste of air.

Float type auto drain allows automatic drain discharge without electric power.





JIS Symbol

Bracket set

Specifications

specifications			
Auto drain type	Float type		
Auto drain valve type	N.O. (Normally open: Open in the case of pressure loss)		
Proof pressure	2.5 MPa		
Max. operating pressure	1.6 MPa		
Operating pressure range Note)	0.05 to 1.6 MPa		
Fluid	Compressed air		
Ambient and fluid temperature	5 to 60°C (With no condensation) <corrosive and="" flammable="" gas="" gas,="" organic="" solvents<br="">are not allowed.></corrosive>		
Max. drain discharge	400 cc/min (Pressure 0.7 MPa, in the case of water)		
Mass	1.2 kg (With bracket: 1.3 kg)		
Paint color	White		
Note) Use for an air compressor with flow more than 50 t/min (ANR).			

Accessory (Option)

<u> </u>	/		
Description	Part no.	Contents	
Bracket set	BM58	Bracket	
Ball valve piping set	ADH-C400	Ball valve/Rc 1/2 1 pc. Barrel nipple/R 1/2 2 pcs. Elbow/Rc 1/2 1 pc.	

Note) Accessory (Option) is included, but not assembled.



Construction



Component Parts

No.	Description	Material	Note
1	Body	Aluminum alloy	Baking finish
2	Housing	Aluminum alloy	Baking finish
3	Drain guard	Aluminum alloy	Baking finish
4	Float	Foam rubber	
5	Pilot valve	Stainless steel + Rubber	
6	Lever	Resin	
7	Flushing button	Brass	
8	Orifice		
9	Diaphragm	Rubber	

Replacement Parts

No.	Description	Part no.	Note
10	Repair kit for main valve	ADH-D400	Kit includes parts from $(10-1)$ to $(10-5)$
11	O-ring	G85(B)	Material: NBR

Note) When changing parts, follow the operating manual. Do not disassemble other parts.

Specific Product Precautions

Be sure to read this before handling. Refer to back pages 1 and 2 for Safety Instructions, "Precautions for Handling Pneumatic Devices" (M-03-E3A) for Common Precautions.

Design

ACaution

1. Use this product in an area where the air pressure does not exceed 1.6 MPa.

If exceeding 1.6 MPa, it could lead to an accident or malfunction.

2. An air pressure of 0.05 MPa and an air compressor's discharge flow rates higher than 50 *d*/min (ANR) are required.

Below these values, the air will be exhausted continuously from the drain exhaust port.

- **3.** Keep the compressed air and the ambient temperature of the location where this product is installed within the range of 5 to 60°C. Exceeding this range could lead to a failure or malfunction.
- 4. Avoid using this product in an area where corrosive gases, flammable gases or organic solvents are contained in the compressed air or in the surrounding air.

Selection

A Caution

1. The maximum dischargeable drainage rate is 400 cc/min. If using this product in excess of this value, there could be causing the drain to flow over to the outlet side. Piping

Caution

- 1. Use piping of 1/2^B or larger for drain inlet and avoid riser piping.
- For drain piping, use a pipe whose I.D. is not less than 8 mm and length not more than 10 m. Do not make any upward angles in drain line. Be sure to secure exhaust port piping since drain is under pressure.

Mounting

\land Caution

1. Install with "out port" down in a vertical position.

Inclination from the vertical line should be less than 5°.

- 2. Install with at least 200 mm of free space above the unit to allow for maintenance.
- **3.** To place this product near the air compressor, install in such a way that the vibrations will not be transmitted.
- 4. Install a valve to drain inlet so that maintenance is possible. Use a ball valve with a bore size of more than 15 mm. (Ball valve piping set is available as an accessory (option).)

ACaution

5. When not draining sufficiently, open the bleed valve so that drain could run through easily.

Mounting

Maintenance

Caution

- 1. Check drain condition periodically (more than once a day). Also, push the flushing button to open the exhaust valve.
- 2. Pilot air is exhausted from the exhaust port indicated in "Dimensions". Do not cover this exhaust port. Clean the exhaust port so that port is not blocked by dust, etc.
- 3. When solid foreign objects exceeding 1 mm come in, the main valve may become blocked. After recovering the internal pressure of this product to 0 MPa (atmospheric pressure), remove the hexagon socket head cap screw (M6) from the body part and wash inside with water to remove foreign solid objects blocking the main valve.
- 4. When using this product, drain may not easily enter the product. In such a case, adjust the open angle of its bleed valve to lower the pressure a bit inside the bowl so that drain could run through easily.

Series ADH4000

Dimensions



Option: Reference Figure of Assembly



Related Products: Differential Pressure Gauge Series GD40-2-01

The pressure differential at the inlet and the outlet of compressed air equipment can be viewed at a glance on the differential pressure gauge. It is ideal for the maintenance control of filters.

Compact and lightweight Can be installed easily by merely providing a bypass circuit. Provided with a protective cover to prevent hazards.



Model/Specifications

Model	GD40-2-01
Fluid	Compressed air
Max. operating pressure	1 MPa
Proof pressure	1.5 MPa
Ambient and fluid temperature	5 to 60°C
Port size Rc	1/8
Scale range	0 to 0.2 MPa
Accuracy	±0.006 MPa
Dial size	ø40
Mass (g)	300

Main Parts Material

Case	Zinc die-casted		Nylon tube	T0425 (0.5 m)
Internal part	Brass, Phosphor bronze	i I	Male connector	H04-01 (1 pc.)
Window	Polyester	j l	Male elbow	DL04-01 (1 pc.)
Scale plate	Stainless steel			

▲ Specific Product Precautions

Accessorv

Be sure to read this before handling.

Refer to back pages 1 and 2 for Safety Instructions, "Precautions for Handling Pneumatic Devices" (M-03-E3A) for Common Precautions.

Design

Mounting

▲Caution

L

L

1. This product cannot be used in a location where pulsations could occur frequently.

Caution

 The HIGH and LOW marks on the back of the differential pressure gauge indicate the high pressure and low pressure sides respectively. Connect the HIGH side to the inlet side of the filter or other devices and the LOW side to their outlet side. Do not use a stop valve to prevent damage to the differential pressure gauge if the valve is inadvertently left open or closed.
 Install the differential pressure gauge vertically.

3) The piping of the differential pressure gauge

Piping Example



Dimensions







Safety Instructions

These safety instructions are intended to prevent hazardous situations and/or equipment damage. These instructions indicate the level of potential hazard with the labels of "**Caution**," "**Warning**" or "**Danger**." They are all important notes for safety and must be followed in addition to International Standards (ISO/IEC), Japan Industrial Standards (JIS)^{*1} and other safety regulations^{*2}).

* 1) ISO 4414: Pneumatic fluid power – General rules relating to systems. ISO 4413: Hydraulic fluid power – General rules relating to systems. IEC 60204-1: Safety of machinery – Electrical equipment of machines. (Part 1: General requirements) ISO 10218-1992: Manipulating industrial robots -Safety. JIS B 8370: General rules for pneumatic equipment. JIS B 9360-1: Safety of machinery – Electrical equipment of machines. (Part 1: General requirements) JIS B 9960-1: Safety of machinery – Electrical equipment of machines. (Part 1: General requirements) JIS B 9933-1993: Manipulating industrial robots - Safety. etc.
* 2) Labor Safety and Sanitation Law, etc.

* 2) Labor Safety and Sanitation Law, etc: **Marning:** Operator error could result in injury or equipment damage. **Marning:** Operator error could result in serious injury or loss of life. **Marning:** In extreme conditions, there is a possibility of serious injury or loss of life.

٦

н

1. The compatibility of the product is the responsibility of the person who designs the equipment or decides its specifications.

Since the product specified here is used under various operating conditions, its compatibility with specific equipment must be decided by the person who designs the equipment or decides its specifications based on necessary analysis and test results. The expected performance and safety assurance of the equipment will be the responsibility of the person who has determined its compatibility with the product. This person should also continuously review all specifications of the product referring to its latest catalog information, with a view to giving due consideration to any possibility of equipment failure when configuring the equipment.

- 2. Only personnel with appropriate training should operate machinery and equipment. The product specified here may become unsafe if handled incorrectly. The assembly, operation and maintenance of machines or equipment including our products must be performed by an operator who is appropriately trained and experienced.
- 3. Do not service or attempt to remove product and machinery/equipment until safety is confirmed.
 - 1. The inspection and maintenance of machinery/equipment should only be performed after measures to prevent falling or runaway of the driven objects have been confirmed.
 - 2. When the product is to be removed, confirm that the safety measures as mentioned above are implemented and the power from any appropriate source is cut, and read and understand the specific product precautions of all relevant products carefully.
 - 3. Before machinery/equipment is restarted, take measures to prevent unexpected operation and malfunction.
- 4. Contact SMC beforehand and take special consideration of safety measures if the product is to be used in any of the following conditions.
 - 1. Conditions and environments outside of the given specifications, or use outdoors or in a place exposed to direct sunlight.
 - 2. Installation on equipment in conjunction with atomic energy, railways, air navigation, space, shipping, vehicles, military, medical treatment, combustion and recreation, or equipment in contact with food and beverages, emergency stop circuits, clutch and brake circuits in press applications, safety equipment or other applications unsuitable for the standard specifications described in the product catalog.
 - 3. An application which could have negative effects on people, property, or animals requiring special safety analysis.
 - 4. Use in an interlock circuit, which requires the provision of double interlock for possible failure by using a mechanical protective function, and periodical checks to confirm proper operation.

SMC

Safety Instructions

The product is provided for use in manufacturing industries.

The product herein described is basically provided for peaceful use in manufacturing industries.

If considering using the product in other industries, consult SMC beforehand and exchange specifications or a contract if necessary. If anything is unclear, contact your nearest sales branch.

Limited Warranty and Disclaimer/Compliance Requirements

The product used is subject to the following "Limited Warranty and Disclaimer" and "Compliance Requirements". Read and accept them before using the product.

Limited Warranty and Disclaimer

1. The warranty period of the product is 1 year in service or 1.5 years after the product is delivered.^{*3)}

Also, the product may have specified durability, running distance or replacement parts. Please consult your nearest sales branch.

- For any failure or damage reported within the warranty period which is clearly our responsibility, a replacement product or necessary parts will be provided. This limited warranty applies only to our product independently, and not to any other damage incurred due to the failure of the product.
- 3. Prior to using SMC products, please read and understand the warranty terms and disclaimers noted in the specified catalog for the particular products.
 - * 3) Vacuum pads are excluded from this 1 year warranty.
 - A vacuum pad is a consumable part, so it is warranted for a year after it is delivered. Also, even within the warranty period, the wear of a product due to the use of the vacuum pad or failure due to the deterioration of rubber material are not covered by the limited warranty.

Compliance Requirements

When the product is exported, strictly follow the laws required by the Ministry of Economy, Trade and Industry (Foreign Exchange and Foreign Trade Control Law).



Series AM /*AFF* **Specific Product Precautions 1**

Be sure to read this before handling. Refer to back pages 1 and 2 for Safety Instructions, and "Precautions for Handling Pneumatic Devices" (M-03-E3A) for Common Precautions.

Design

1. Design the layout so that the mist separator should be installed in an area that is less susceptible to pulsations.

The element could be damaged if a difference between the inlet pressure and the outlet pressure exceeds 0.1 MPa.

2. Be careful of dust generation by the pneumatic equipment mounted on the outlet side.

When installing pneumatic equipment on the outlet side of the AM⁻ series, dust particles may come off from outlet equipment, which will lower the cleanliness of compressed air. Consider this impact upon the cleanliness of compressed air when installing pneumatic equipment on the outlet side.

3. About when to use N.C. auto drain and N.O. auto drain.

When using the AFF2C to 22C, 37B, 75B, AM⊡150C to 550C, 650, 850 with normally open (N.O.) auto drain, air may ceaselessly blow out of the drain discharge area when an air compressor with a small air discharge volume is used since the valve does not close unless the air pressure is 0.1 MPa or higher. Therefore, when using a compressor for 3.7 kW or less, make sure to use the normally closed (N.C.) auto drain. The minimum operating pressure is 0.15 MPa even with N.C. auto drain.

4. Use a tubing with proper size and length for drain piping of auto drain.

When using the AFF2C to 22C, 37B, AM□150C to 550C, 650 with auto drain:

Normally closed (N.C.) $\Big]$ Use tubing O.D. 10 mm and keep Normally open (N.O.) $\Big]$ the whole length within 5 m.

When using the AFF75B and AM 850 with auto drain:

Normally open (N.O.): Use tubing I.D. 9 mm or more and keep the whole length within 2.8 m.

5. Provide a design that prevents back pressure and back flow.

Back pressure or back flow may damage an element.

6. Keep the certificate of Class 2 Pressure Vessel in a safe place.

Products below are subject to Class 2 Pressure Vessel Act. Certificate will be sent in 2 to 4 weeks later after the shipment of the product.

Main Line Filter AFF220A

Micro Mist Separator AMD900/100/901

≜ Warning

1. Hold the female thread side and tighten to the recommended torque when screwing in the piping material.

Insufficient tightening torque may cause loosening or defective sealing. Over-tightening torque may damage the thread etc. If it is tightened without holding the female thread side, excessive force will be directly applied to the piping bracket resulting in a product failure.

Recommended Torque Unit: N·m								
Connection thread	1/8	1/4	3/8	1/2	3/4	1	1 1⁄2	2
Torque	1.5 to 2	7 to 9	12 to 14	28 to 30	28 to 30	36 to 38	48 to 50	48 to 50

* After tightening manually, tighten additionally by about 1/6 turn with a tightening tool.



2. Do not apply torsional moment or bending moment (except the product's own weight) to the bracket. It may damage the bracket. Support external piping separately.



3. Inflexible piping such as steel piping tends to be affected by spread of excessive moment load or vibration from the piping side. Lay flexible tubing between the steel pipe and the product to prevent such effects.



Series AM /*AFF* **Specific Product Precautions 2**

Be sure to read this before handling. Refer to back pages 1 and 2 for Safety Instructions, and "Precautions for Handling Pneumatic Devices" (M-03-E3A) for Common Precautions.

Selection

1. About the system composition of purifying compressed air

Compressed air generally contains particulate contaminants as listed below, though there are some variations due to the compressor type and specifications. Determine the system configuration according to the desired cleanliness of compressed air and application, while referring to the "Air Preparation Equipment Selection Guide" for the AM□ series (Best Pneumatics).

[Particulate contaminants in compressed air]

- Water (drainage)
- Dust sucked from ambient air
- Degenerated oil from compressor
- Solid foreign matter such as rust inside piping and oil

2. Select according to the maximum flow consumption.

When compressed air is used for air blow, etc., find the maximum air consumption before selecting the size of the $AM\Box$ series. (If compressed air exceeding the maximum flow rate is supplied, it can result in decline of the cleanliness of compressed air or element damage.)

Mounting

1. About the mounting orientation of the products

Make sure to install this product on horizontal piping. If it is installed diagonally, laterally, or upside down, the drain separated by the element will splash to the outlet side. Piping

1. Connect it with IN and OUT ports in proper location. It does not work with the connection reversed.

In the case of the AFF2C to 22C, 37B, 75B, AM⊡150C to 550C, 650, 850

Verify the direction of the flow of the compressed air and the " \Box ?" or " \triangleright " mark that indicates the inlet of the product before connecting. It cannot be used if connected in the opposite direction.



In the case of the AFF75A to 220A, AMD801, 901, 800, 900, 1000

INLET and OUTLET of compressed air is labeled on the side of flange. Be sure to connect correctly.

2. Use an air blower to flush the piping before connecting the piping.

Use an air blower to thoroughly flush the piping, or wash the piping to remove any cutting chips, cutting oil, or debris from inside the piping before connecting them.

3. Wrapping of sealant tape

When screwing in the pipes or fittings, make sure to prevent cutting chips or the sealant material on the threaded portion of the pipe from entering the piping. If sealant tape is to be used, leave about 1.5 to 2 ridges of threads uncovered.

4. Modular connection

Mount the attached bracket on one side when connecting 2 sets. Mount the attached brackets on both sides when connecting 3 sets or more. As a guideline for the number of brackets, one bracket should be mounted for every 2 products.



Series AM / AFF Specific Product Precautions 3

Be sure to read this before handling. Refer to back pages 1 and 2 for Safety Instructions, and "Precautions for Handling Pneumatic Devices" (M-03-E3A) for Common Precautions.

Air Supply

1. The mist separator is not applicable to gases other than compressed air.

The mist separator is not applicable to gases other than compressed air (example: oxygen, hydrogen, flammable gas, mixed gas).

2. Do not use compressed air that contains chemicals, organic solvents, salt, or corrosive gases.

Do not use compressed gas containing chemicals, organic solvents, salt or corrosive gas. This can cause rust, damage to rubber and resin parts, or malfunction.

3. Operate within the specified operating pressure range.

Damage, failure, or malfunction may occur if the mist separator is operated above the maximum operating pressure.

If the mist separator is used below the minimum operating pressure, increase in the air-flow resistance due to clogging will have such influence that the desired flow rate cannot be obtained.

If the mist separator is used under a low pressure such as for a blower, conduct sufficient tests by users to confirm the specifications and performances.

Operating Environment

ACaution

1. Do not use in the following environments, as this can cause failure.

- In locations having corrosive gases, organic solvents, and chemical solutions, or in locations where these elements are likely to adhere to the equipment.
- 2) In locations where salt water, water, or water vapor could come in contact with the equipment.
- 3) In locations that is exposed to shocks and vibrations.
- 2. Be careful about the contamination of the workpieces due to entrainment of the ambient air.

If compressed air is used for air blow, compressed air blowing out from the blow nozzle may entrain foreign matter (solid particles and liquid particles) floating in the ambient air, blowing it against the workpieces and causing adhesion. Therefore, sufficient precautions must be taken about the ambient environment. Maintenance

▲Caution

1. Replace the element immediately when the time for its replacement has arrived.

To replace the element, replace the O-ring and the gasket, too. For the replacement procedure, refer to the operating manual. (For element dimensions, refer to back page 6.)

<Element replacement>

In the case of the AFF2C to 22C, 37B, 75B, AM $\Box150C$ to 550C, 650, 850

The replacement interval for the element is when the pressure drop reaches 0.1 MPa or after two years of operation, whichever comes first. A pressure drop can be verified with the element service indicator (-T) or with differential pressure gauge (Made to Order).

In the case of the AFF75A to 220A, AMD800 to 1000, AMD801, 901

The replacement interval for the element is when the pressure drop reaches 0.1 MPa or after one year of operation, whichever comes first. Confirm the pressure drop with a pressure gauge. (With pressure gauge: -G)

2. Be sure to exhaust the drain accumulated in the filter container.

Failure to discharge the drain will allow the accumulated drain to flow over to the outlet side.

When using the AFF2C to 22C, 37B, 75B, AM□150C to 550C, 650, 850 with drain cock, drain guide or ball valve, discharge the drain before the drainage level reaches the center of the sight glass. If the drain is not discharged properly, it will flow over to the outlet side.





Series AM / AFF Specific Product Precautions 4

Be sure to read this before handling. Refer to back pages 1 and 2 for Safety Instructions, and "Precautions for Handling Pneumatic Devices" (M-03-E3A) for Common Precautions.

Maintenance

ACaution

3. In the case of a type with auto drain

- The auto drain operates when the drainage level reaches the top of the sight glass, and the drain will be discharged.
- When using the AFF2C to 22C, 37B, AM□150C to 550C, 650 with auto drain, the drain is automatically discharged with the knob tightened to the "S" side. Manual drain discharge, however, is also possible.

<Manual operation>

A manual knob attached to the auto drain end is tightened to the "S" side in normal operation. The drain can be discharged by loosening it to the "O" side. (Be careful, however, if pressure remains inside the filter when the drain is discharged, the drain will blow out from the drain port.)



4. The drain exhaust parts replacement method and necessary parts are different depending on when it was manufactured.

	Necessa	Applicable size	
Description	Manufactured Manufactured Dec. 2002 or before Jan. 2003 onwards [Up to manufacturing [Manufacturing lot No.		
	lot No. GZ]	HO onwards]	
Drain cock	AM-S	00 10 000	
Drain guide	AM-S	2C to 22C	
N.O. auto drain	Auto drains cannot be replaced alone since those cannot be	AD43PA-D	2B to 37B 150C to 550C 150 to 650
N.C. auto drain	assembled without dedicated assembly tools. The entire bowl assembly must be replaced. (Refer to "How to Order Bowl Assembly" on page 63.)	AD53PA-D	2C to 22C 2B to 22B 150C to 550C 150 to 550
Ball valve set	AM-SA	75B. 850	
N.O. auto drain	AD34P/		

Note) Jig (AM-SA005) for replacing auto drain is necessary for the 75B or 850.

Others

▲Caution

1. Element interchange

Following is the element dimensions for the AFF and $\mathsf{AM}\square$ series:

Since elements for the same body size has the same dimensions, they are interchangeable.

However, do not interchange them easily since it can cause various kinds of problems.

If interchanging the elements is unavoidable, replace the product model number label, too.



Element Dimensions

Model	Element dimensions (Reference value)		
	øA	В	
AFF2C, AFF2B, AM150C, AM150 AMD150C, AMD150, AMH150C, AMH150	49	42	
AFF4C, AFF4B, AM250C, AM250 AMD250C, AMD250, AMH250C, AMH250	58	52	
AFF8C, AFF8B, AM350C, AM350 AMD350C, AMD350, AMH350C, AMH350	70	78	
AFF11C, AFF11B, AM450C, AM450 AMD450C, AMD450, AMH450C, AMH450	82	88	
AFF22C, AFF22B, AM550C, AM550 AMD550C, AMD550, AMH550C, AMH550	96	118	
AFF37B, AM650 AMD650, AMH650	122	144	
AFF75B, AM850 AMD850, AMH850	142	223	

2. About oil-free products

The AFF and $AM\Box$ series includes parts (such as resin parts, rubber parts, and elements) that does not allow degreasing wash. Therefore, oil-free products with all parts degreasing washed is not available.

3. Degreasing wash

Certain parts such as the body and housing can be degreasing washed. Contact SMC after confirming the specifications. (available as Option or Made to Order)

4. Change of oil

On the AFF and $AM\Box$ series, no oil such as grease is applied to parts exposed to compressed air. However, for certain specifications, there are some parts to which oil is applied. It is possible to change the type of applied oil (as Option or Made to Order).



Series AM /*AFF* // *Specific Product Precautions 5*

Be sure to read this before handling. Refer to back pages 1 and 2 for Safety Instructions, and "Precautions for Handling Pneumatic Devices" (M-03-E3A) for Common Precautions.

Others

ACaution

5. Internal volume of filter container

The product can be used as a small capacity air tank by removing the element.

Following is the volume of filter containers of the AFF and $AM\Box$ series (when the element is removed).

Volume Inside Filter

Model	Volume inside filter (Reference value) (cm ³)
AFF2C, AFF2B, AM150C, AM150 AMD150C, AMD150, AMH150C, AMH150	250
AFF4C, AFF4B, AM250C, AM250 AMD250C, AMD250, AMH250C, AMH250	300
AFF8C, AFF8B, AM350C, AM350 AMD350C, AMD350, AMH350C, AMH350	600
AFF11C, AFF11B, AM450C, AM450 AMD450C, AMD450, AMH450C, AMH450	1000
AFF22C, AFF22B, AM550C, AM550 AMD550C, AMD550, AMH550C, AMH550	1500
AFF37B, AM650 AMD650, AMH650	3000
AFF75B, AM850 AMD850, AMH850	9000

Discontinued Model and Equivalent Model

The AFF and AM^{\Box} series were remodeled to products introduced in this catalog in 1988. Along with the new models, old models were provided mainly for the purpose of maintenance. However, due to the aging of metal dies and extreme decline in the quantity, the procurement of parts and consequently the maintenance of the production system became difficult. For this reason, old models were discontinued in 1994, as detailed in the table below. Use the equivalent model listed there.

Discontinued Model and Equivalent Model

	Production discontinuance				Equivalent model		
Product name	Model	Period of production discontinuance for products	Period of production discontinuance for maintenance parts	External dimensions of product Width x Depth x Height	Model	External dimensions of product Width x Depth x Height	Page
	AFF6		End of March '99	100 x 100 x 253	AFF4C	76 x 76 x 172	P.10
Main Line Filter	AFF22			150 x 140 x 446	AFF22C	122 x 122 x 259	
	AFF37			200 x 170 x 526	AFF37B	160 x 160 x 311	
	AFF55			280 x 280 x 497	AFF75B	220 x 220 x 461	
	AM200	End of July '94		63 x 63 x 191	AM150C	63 x 63 x 158	P.18
	AM300			85 x 85 x 258	AM250C	76 x 76 x 172	
Mist Separator	AM400			120 x 120 x 236	AM350C	90 x 90 x 204	
	AM500			140 x 140 x 383	AM550C	122 x 122 x 259	
	AM600			180 x 170 x 465	AM650	160 x 160 x 311	
	AMD100			63 x 63 x 136	AMD150C	63 x 63 x 158	P.26
Micro Mist Separator	AMD200			80 x 82 x 170	AMD250C	76 x 76 x 172	
	AMD300			90 x 90 x 233	AMD350C	90 x 90 x 204	
	AMD400			140 x 140 x 380	AMD450C	106 x 106 x 225	
	AMD500			140 x 140 x 490	AMD550C	122 x 122 x 259	
	AMD600			140 x 140 x 590	AMD650	160 x 160 x 311	
Odor Removal Filter	AMF200			80 x 80 x 153	AMF250C	76 x 76 x 103	-
	AMF300			90 x 90 x 216	AMF350C	90 x 90 x 132	
	AMF400			140 x 140 x 250	AMF450C	106 x 106 x 151	P.52
	AMF500			140 x 140 x 360	AMF550C	122 x 122 x 187	
	AMF600			140 x 140 x 460	AMF650	160 x 160 x 291	

Note) Some models have different heights depending on the port size. They are shown in parentheses.



SMC'S GLOBAL MANUFACTURING, DISTRIBUTION AND SERVICE NETWORK



EUROPE

AUSTRIA SMC Pneumatik GmbH (Austria) BELGIUM

SMC Pneumatics N.V./S.A. BULGARIA SMC Industrial Automation Bulgaria Eood

CROATIA SMC Industrijska Automatika d.o.o.

CZECH REPUBLIC SMC Industrial Automation CZ s.r.o. DENMARK

SMC Pneumatik A/S

SMC Pneumatics Estonia OÜ FINLAND

SMC Pneumatics Finland Oy **FRANCE**

SMC Pneumatique SA

SMC Pneumatik GmbH GREECE

SMC Hellas E.P.E. HUNGARY

SMC Hungary Ipari Automatizálási Kft. IRELAND SMC Pneumatics (Ireland) Ltd. ITALY SMC Italia S.p.A. LATVIA SMC Pnuematics Latvia SIA LITHUANIA

UAB "SMC Pneumatics"

NETHERLANDS

SMC Pneumatics B.V. NORWAY SMC Pneumatics Norway AS POLAND SMC Industrial Automation Polska Sp.z.o.o. ROMANIA SMC Romania S.r.I.

RUSSIA SMC Pneumatik LLC

SLOVAKIA SMC Priemyselná Automatizácia Spol s.r.o. SLOVENIA SMC Industrijska Avtomatika d.o.o. SPAIN/PORTUGAL SMC España S.A.

SWEDEN SMC Pneumatics Sweden AB SWITZERLAND SMC Pneumatik AG

U.K. SMC Pneumatics (U.K.) Ltd.

ASIA

CHINA SMC (China) Co., Ltd. HONG KONG SMC Pneumatics (Hong Kong) Ltd. INDIA SMC Pneumatics (India) Pvt. Ltd. MALAYSIA SMC Pneumatics (S.E.A.) Sdn. Bhd. PHILIPPINES Shoketsu SMC Corporation SINGAPORE SMC Pneumatics (S.E.A.) Pte. Ltd. SOUTH KOREA SMC Pneumatics Korea Co., Ltd. TAIWAN SMC Pneumatics (Taiwan) Co., Ltd. THAILAND SMC (Thailand) Ltd.

NORTH AMERICA -

CANADA SMC Pneumatics (Canada) Ltd. MEXICO SMC Corporation (Mexico), S.A. de C.V. U.S.A. SMC Corporation of America

SOUTH AMERICA -

ARGENTINA SMC Argentina S.A. BOLIVIA SMC Pneumatics Bolivia S.r.I. BRAZIL SMC Pneumáticos do Brasil Ltda CHILE SMC Pneumatics (Chile) S.A. VENEZUELA SMC Neumatica Venezuela S.A.

OCEANIA

AUSTRALIA SMC Pneumatics (Australia) Pty. Ltd. NEW ZEALAND SMC Pneumatics (N.Z.) Ltd.

Safety Instructions Be sure to read "Precautions for Handling Pneumatic Devices" (M-03-E3A) before using.

SMC Corporation

Akihabara UDX 15F, 4-14-1, Sotokanda, Chiyoda-ku, Tokyo 101-0021, JAPAN Phone: 03-5207-8249 Fax: 03-5298-5362 URL http://www.smcworld.com © 2008 SMC Corporation All Rights Reserved

Specifications are subject to change without prior notice and any obligation on the part of the manufacturer. D-DN 1st printing MT printing MT 16400DN Printed in Japan. This catalog is printed on recycled paper with concern for the global environment.